

Pebble Step Sof-Tred™ Anti-Fatigue Mat 3' x 5'

FLM127 For Light Chemical Splash, For Light Oil/Grease Splash, 3' x 5' x .375"

Dyna-Shield coating guards against chemical splashes and moisture penetration.

- 3/8" thick PVC sponge base reduces leg stress and strain
- Protective Dyna-Shield coating provides longevity, surface durability and chemical resistance
- Rounded edges and a pebble-top surface prevent slips or trips
- High-visibility yellow ramp increases visibility
- Beveled edges help reduce tripping hazard



Specifications

| | |
|--------------------------------|-------------------------------|
| Dimensions | 3' W x 5' L x .375" H |
| Chemical Contact | For Light Chemical Splash |
| Oil/Grease Contact | For Light Oil/Grease Splash |
| Application | Dry Applications |
| Anti-Slip | Yes |
| Beveled Edge | Yes |
| Color | Black w/ Yellow Border |
| Brand | NoTrax |
| Drainage Holes | Without Holes |
| Grit Surface | No |
| Safe for Welding Areas | No |
| Static-Dissipative | No |
| Distributor Part Number | 10860-114;4311123;04088x66544 |
| Sold as | 1 each |

| | |
|-----------------------------|-------------------------|
| Weight | 11 lbs. |
| # per Pallet | 56 |
| Composition | Dyna-Shield® PVC Sponge |
| UNSPSC | 52101510 |
| Pigalog® Page Number | <u>Page 232</u> |

Metric Equivalent

| | |
|-------------------|--------------------------------|
| Dimensions | 91.4cm W x 152.4cm L x 9.5mm H |
| Weight | 5 kg |

Technical Information

Technical Documents

NoTrax® Floor Matting



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com