

Pebble Step Sof-Tred™ Anti-Fatigue Mat Custom 3' Roll



FLM129 For Light Chemical Splash, For Light Oil/Grease Splash, 3' x .375"

Dyna-Shield coating guards against chemical splashes and moisture penetration.

- 3/8" thick PVC sponge base reduces leg stress and strain
- Protective Dyna-Shield coating provides longevity, surface durability and chemical resistance
- Rounded edges and a pebble-top surface prevent slips or trips
- High-visibility yellow ramp increases visibility
- Beveled edges help reduce tripping hazard
- Custom length lets your mat match your workplace with clean, factory-cut edges



Item#	Description	Dimensions	Weight
FLM129-CLR	Custom Length Roll	3' W x .375" H	2.25 lbs.

Metric Equivalent:

Item#	Description	Dimensions	Weight
FLM129-CLR	Custom Length Roll	91.4cm W x 9.5mm H	1 kg

Specifications

Dimensions	3' W x .375" H
Chemical Contact	For Light Chemical Splash
Oil/Grease Contact	For Light Oil/Grease Splash
Application	Dry Applications
Anti-Slip	Yes
Beveled Edge	Yes
Color	Black w/ Yellow Border
Brand	NoTrax

Drainage Holes	Without Holes
Grit Surface	No
Safe for Welding Areas	No
Static-Dissipative	No
Sold as	1 each
Weight	2.25 lbs.
# per Pallet	1
Composition	Dyna-Shield® PVC Sponge
UNSPSC	52101510
Pigalog® Page Number	<u>Page 236</u>

Metric Equivalent

Dimensions	91.4cm W x 9.5mm H
Weight	1 kg

Technical Information

Technical Documents

NoTrax® Floor Matting



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com