





# PIG® TuffGrit<sup>™</sup> Step Cover with Extra © Coarse Grit

FLM3018 3" W x 30" L x 1" H,Install With Adhesive or Mechanical Fasteners,1 each

Anti-slip step treads add traction in rugged environments, even in wet or oily conditions. Rigid fiberglass Stair Tread Covers with TuffGrit™ texture easily outperform rubber and vinyl treads, paints and tapes.

- Durable fiberglass step cover with proprietary TuffGrit™ extra coarse texture is 0.26" thick for use in high-traffic areas or heavy industrial environments
- Cover wraps around stair nosing to provide excellent footing where most slips occur
- Aggressive anti-slip step tread adds reliable traction, even in wet or oily conditions, far exceeding ANSI standards
- Resists UV, chemicals, corrosion and heavy traffic for long-lasting protection, indoors or out
- Pre-cut Step Covers can be installed on steel and composite grating, steel and aluminum plate, concrete or wood (fasteners and adhesive not included)
- Available Glo Yellow option adds visibility in low-light conditions
- Ask us about custom sizes, colors and personalization

Item#	Description	Dimensions	Weight
FLM3018-GDY		3" W x 30" L x 1" H	1.65 lbs.
FLM3018-YW		3" W x 30" L x 1" H	1.65 lbs.

### Metric Equivalent:

Item#	Description	Dimensions	Weight
FLM3018-GDY		7.6cm W x 76cm L x 2.5cm H	.7 kg
FLM3018-YW		7.6cm W x 76cm L x 2.5cm H	.7 kg

#### **Specifications**

Dimensions	3" W x 30" L x 1" H
Brand	PIG
Installation Method	Adhesive or Mechanical Fasteners
Sold as	1 each
Weight	1.65 lbs.

**Fiberglass** 

Composition

	Aluminum Oxide
UNSPSC	30162104
Pigalog® Page Number	Page 242

## Metric Equivalent

Weight .7 kg

**Dimensions** 7.6cm W x 76cm L x 2.5cm H

#### **Technical Information**

#### **Certifications, Approvals and Ratings**

NFSI Certified



# One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com