

# PIG® TuffGrit™ Anti-Slip Walkway <sup>®</sup> Cover

FLM5001 3' W x 5' L,Install With Adhesive or Mechanical Fasteners,1 per box

Add a high-traction surface to walkways or ramps where slip-and-fall hazards are a concern. Longlasting TuffGrit™ texture helps keep workers and visitors on their feet, even in wet or oily conditions.

- Proprietary TuffGrit<sup>™</sup> texture adds reliable traction, even in wet or oily conditions, far exceeding ANSI standards
- Superior, longer-lasting solution compared to gritted paints, treads and tapes
- Durable fiberglass construction is built to withstand high foot traffic and abuse from industrial applications
- Resists UV, chemicals, corrosion, and impact for long-lasting protection, indoors or out
- Can be installed on steel and composite grating, steel and aluminum plate, concrete or wood (fasteners and adhesive not included)
- Available Glo Yellow option adds visibility in low-light conditions
- Ask us about custom sizes, colors and personalization

Item#	Description	Dimensions	Weight
FLM5001-BK		3' W x 5' L	39.75 lbs.
FLM5001-BWY		3' W x 5' L	39.75 lbs.
FLM5001-GBY		3' W x 5' L	39.75 lbs.
FLM5001-YW		3' W x 5' L	39.75 lbs.

### Metric Equivalent:

Item#	Description	Dimensions	Weight
FLM5001-BK		91cm W x 152cm L	18 kg
FLM5001-BWY		91cm W x 152cm L	18 kg
FLM5001-GBY		91cm W x 152cm L	18 kg
FLM5001-YW		91cm W x 152cm L	18 kg

### **Specifications**

Dimensions	3' W x 5' L	
Brand	PIG	
Installation Method	Adhesive or Mechanical Fasteners	

Sold as 1 per box

Weight	39.75 lbs.
# per Pallet	10
Composition	Fiberglass Aluminum Oxide
UNSPSC	25191533
Pigalog® Page Number	Page 243

## Metric Equivalent

Weight 18 kg

**Dimensions** 91cm W x 152cm L

## **Technical Information**

## **Certifications, Approvals and Ratings**

**NFSI** Certified



## One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com