



Non-Skid Step Tape

FLM640 2" x 60', 1 roll

Durable mineral grit helps create safe footing anywhere.

- Helps create a non-skid surface for safe footing throughout your facility
- Grit is sealed with 2-part epoxy resin for durability and to prevent shedding
- Resists oil, water and heavy foot traffic for long service life
- Adhesive features low initial tack for minutes of easy repositioning
- Tape removes without residue
- Just cut to length, remove protective backing and apply



Item#	Description	Dimensions	Weight
FLM640-BK		2" W x 60' L	1.71 lbs.
FLM640-HZ		2" W x 60' L	1.71 lbs.
FLM640-SY		2" W x 60' L	1.71 lbs.

Metric Equivalent:

Item#	Description	Dimensions	Weight
FLM640-BK		5.1cm W x 18m L	.8 kg
FLM640-HZ		5.1cm W x 18m L	.8 kg
FLM640-SY		5.1cm W x 18m L	.8 kg

Specifications

Dimensions	2" W x 60' L
Brand	Incom
Installation Method	Self-Adhesive
Thickness	30 mil Black, 25 mil Hazard & Yellow
Sold as	1 roll
Weight	1.71 lbs.

Composition	30 mil Black - Mineral-Abrasive Compound; 25 mil Hazard & Yellow Mineral-Abrasive Compound
--------------------	--

UNSPSC	31201513
---------------	----------

Pigalog® Page Number	<u>Page 228</u>
-----------------------------	-----------------

Metric Equivalent

Dimensions	5.1cm W x 18m L
-------------------	-----------------

Weight	.8 kg
---------------	-------

Technical Information

Certifications, Approvals and Ratings

NFSI Certified



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com