



Non-Skid Step Tape

FLM642 6" x 60', 1 roll

Durable mineral grit helps create safe footing anywhere.

- Helps create a non-skid surface for safe footing throughout your facility
- Grit is sealed with 2-part epoxy resin for durability and to prevent shedding
- Resists oil, water and heavy foot traffic for long service life
- Adhesive features low initial tack for minutes of easy repositioning
- Tape removes without residue
- Just cut to length, remove protective backing and apply



Item#	Description	Dimensions	Weight
FLM642-BK		6" W x 60' L	5.42 lbs.
FLM642-HZ		6" W x 60' L	5.42 lbs.

Metric Equivalent:

Item#	Description	Dimensions	Weight
FLM642-BK		15.2cm W x 18m L	2.5 kg
FLM642-HZ		15.2cm W x 18m L	2.5 kg

Specifications

Dimensions	6" W x 60' L
Brand	Incom
Installation Method	Self-Adhesive
Thickness	30 mil Black, 25 mil Hazard & Yellow
Distributor Part Number	6906080;4213023;4619844;04088x64255
Sold as	1 roll

Weight	5.42 lbs.
# per Pallet	390
Composition	30 mil Black - Mineral-Abrasive Compound; 25 mil Hazard & Yellow Mineral-Abrasive Compound
UNSPSC	31201513
Pigalog® Page Number	<u>Page 237</u>

Metric Equivalent

Dimensions	15.2cm W x 18m L
Weight	2.5 kg

Technical Information

Certifications, Approvals and Ratings

NFSI Certified

Technical Documents

29 CFR 1910.24(f)

29 CFR 1910.26(a)(1)(v)



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com