




# Cushion Trax® Anti-Fatigue Mat Custom 3' Roll

FLM666 For Light Chemical Splash, For Light Oil/Grease Splash, 3' x .562"

With a diamond plate top and a RedStop bottom that clings to even smooth floors, this anti-fatigue mat great for preventing slips in light splash areas.

- Built-in RedStop technology clings to floors including painted or sealed concrete, vinyl and ceramic tile
- Durable vinyl top construction features a diamond plate top surface for multi-directional slip resistance
- Dense, closed-cell PVC foam base provides cushioning to help increase comfort
- Beveled edges help reduce tripping hazard
- Solid-surface design is ideal for dry workstations
- Custom length lets your mat match your workplace with clean, factory-cut edges



Item#	Description	Dimensions	Weight
FLM666-BK-CLR	Black, Custom Length Roll	3' W x .562" H	4.08 lbs.
FLM666-BWY-CLR	Black w/ Yellow Border, Custom Length Roll	3' W x .562" H	4.08 lbs.

**Metric Equivalent:**

Item#	Description	Dimensions	Weight
FLM666-BK-CLR	Black, Custom Length Roll	91.4cm W x 1.4cm H	1.9 kg
FLM666-BWY-CLR	Black w/ Yellow Border, Custom Length Roll	91.4cm W x 1.4cm H	1.9 kg

**Specifications**

<b>Static-Dissipative</b>	No
<b>Drainage Holes</b>	Without Holes
<b>Anti-Slip</b>	Yes
<b>Dimensions</b>	3' W x .562" H
<b>Chemical Contact</b>	For Light Chemical Splash
<b>Oil/Grease Contact</b>	For Light Oil/Grease Splash
<b>Maximum Order Length</b>	75

<b>Minimum Order Length</b>	2
<b>Beveled Edge</b>	Yes
<b>Brand</b>	NoTrax
<b>Grit Surface</b>	No
<b>Safe for Welding Areas</b>	No
<b>Sold as</b>	1 foot
<b>Weight</b>	4.08 lbs.
<b>Composition</b>	Top Coat - Vinyl Cushion - PVC
<b>Application</b>	Dry Applications
<b>UNSPSC</b>	52101510
<b>Pigalog® Page Number</b>	<u>Page 239</u>

## Metric Equivalent

<b>Dimensions</b>	91.4cm W x 1.4cm H
<b>Weight</b>	1.9 kg

## Technical Information

### Certifications, Approvals and Ratings

NFSI Certified

### Technical Documents

[NoTrax® Floor Matting](#)

### Disclaimers

#### Nominal Anti-Fatigue Mat Dimensions

Mat sizes are approximate as rubber shrinks and expands in conjunction with temperature and time. Tolerable manufacturing size variance is 3-5%.



**One Pork Avenue • Tipton, PA 16684-0304**

1-855-493-4647 • Fax: 1-800-621-7447 • [newpig.com](http://newpig.com) • [hothogs@newpig.com](mailto:hothogs@newpig.com)