

Diamond-Deluxe™ with Grit-Safe™ Anti-Fatigue Mat 3' x 5'

FLM830 For Light Chemical Splash, For Light Oil/Grease Splash, 3' x 5' x 0.5"

Make footing in wet, slippery workstations safer and drier with this open-loop, anti-fatigue "spaghetti mat."

- Open-loop, flow-through design allows liquids to pass through the entire mat surface; provides better drainage than mats with punched holes
- Elevates feet out of wet, oily environments to promote a drier work surface and minimize tracking through your facility
- Diamond embossed surface is impregnated with non-slip grit for extra traction to minimize slips and falls
- Durable vinyl construction resists water and most oils; ideal for use in wet, slippery areas in factories, garages and steel mills
- Anti-fatigue properties reduce leg stress and back strain



CROWN

| Item# | Description | Dimensions | Weight |
|-----------|-------------|----------------------|---------|
| FLM830-BK | Black | 3' W x 5' L x 0.5" H | 17 lbs. |

Metric Equivalent:

| Item# | Description | Dimensions | Weight |
|-----------|-------------|---------------------------------|--------|
| FLM830-BK | Black | 91.4cm W x 152.4cm L x 12.7mm H | 7.7 kg |

Specifications

| | |
|--------------------|-----------------------------|
| Static-Dissipative | No |
| Drainage Holes | With Holes |
| Anti-Slip | Yes |
| Dimensions | 3' W x 5' L x 0.5" H |
| Chemical Contact | For Light Chemical Splash |
| Oil/Grease Contact | For Light Oil/Grease Splash |
| Beveled Edge | No |
| Brand | Crown |
| Grit Surface | Yes |

| | |
|------------------------|------------------|
| Safe for Welding Areas | No |
| Sold as | 1 each |
| Weight | 17 lbs. |
| Composition | Vinyl |
| Application | Wet Applications |
| UNSPSC | 52101510 |
| Pigalog® Page Number | <u>Page 239</u> |

Metric Equivalent

| | |
|------------|---------------------------------|
| Dimensions | 91.4cm W x 152.4cm L x 12.7mm H |
| Weight | 7.7 kg |

Technical Information

Technical Documents

[Crown Mats](#)

Disclaimers

Nominal Anti-Fatigue Mat Dimensions

Mat sizes are approximate as rubber shrinks and expands in conjunction with temperature and time. Tolerable manufacturing size variance is 3-5%.



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com