



## PIG® TuffGrit™ Diamond Plate Anti-Fatigue Mat

FLM8502 Dry Applications, Cushion: Vinyl & PVC Foam/Top Coat: Aluminum Oxide and Proprietary Sealant, 3' W x 5' L

Grit so tough it lasts 11X longer! The TuffGrit™ surface on our Diamond Plate Anti-Fatigue Mat easily outlasts the competition, providing long-lasting traction in slippery environments.

- Proprietary TuffGrit™ coating is incredibly durable and abrasion resistant; lasts up to eleven times longer than the leading competitor's grit coating in dry environments, and up to seven times longer under oily conditions
- Exceeds ANSI standards for high slip resistance, providing extreme traction even in wet areas or applications with light overspray or oily drips (not for use in standing water/oil)
- Engineered to leave no grit behind; safer than other mats that gradually lose their grit -- and their effectiveness -- over time
- Raised diamond plate texture adds a second level of slip resistance in addition to TuffGrit™ coating
- More than a half inch of PVC foam relieves stress on knees, feet, ankles and back from extended standing
- Reinforced industrial grade construction is built to last in heavy-duty applications
- Built-in beveled edges create a safe transition on and off mat

Item#	Description	Dimensions	Weight
FLM8502-BK		3' W x 5' L x .563" H	24 lbs.
FLM8502-BWY		3' W x 5' L x .563" H	24 lbs.

### Metric Equivalent:

Item#	Description	Dimensions	Weight
FLM8502-BK		91cm W x 152cm L x 1.4cm H	10.9 kg
FLM8502-BWY		91cm W x 152cm L x 1.4cm H	10.9 kg

### Specifications

<b>Size</b>	3' W x 5' L
<b>Dimensions</b>	3' W x 5' L x .563" H
<b>Chemical Contact</b>	For Light Chemical Splash

<b>Oil/Grease Contact</b>	For Light Oil/Grease Splash
<b>Anti-Slip</b>	Yes
<b>Application</b>	Dry Applications
<b>Beveled Edge</b>	Yes
<b>Brand</b>	PIG
<b>Drainage Holes</b>	Without Holes
<b>Grit Surface</b>	Yes
<b>Safe for Welding Areas</b>	No
<b>Static-Dissipative</b>	No
<b>Sold as</b>	1 each
<b>Weight</b>	24 lbs.
<b># per Pallet</b>	56
<b>Composition</b>	Cushion: Vinyl & PVC Foam Top Coat: Aluminum Oxide and Proprietary Sealant
<b>UNSPSC</b>	52101510
<b>Pigalog® Page Number</b>	<a href="#">Page 231</a>

## Metric Equivalent

<b>Weight</b>	10.9 kg
<b>Dimensions</b>	91cm W x 152cm L x 1.4cm H

## Technical Information

### Technical Documents

[PIG Anti-Fatigue Mat](#)

[Instructions for PIG Anti-Fatigue Matting](#)



**One Pork Avenue • Tipton, PA 16684-0304**

1-855-493-4647 • Fax: 1-800-621-7447 • [newpig.com](http://newpig.com) • [hothogs@newpig.com](mailto:hothogs@newpig.com)