

PIG® TuffGrit™ Comfort Anti-Fatigue Mat

FLM8504 Dry Applications, Cushion: PVC Foam/Top Coat: Aluminum Oxide and Proprietary Sealant, 3' W x 5' L

Durable TuffGrit™ surface on this comfortable antifatigue mat provides long-lasting traction in slippery environments.

- Proprietary TuffGrit[™] coating is incredibly durable and abrasion resistant; no other grit coating on the market lasts longer
- Exceeds ANSI standards for high slip resistance, providing extreme traction even in wet areas or applications with light overspray or oily drips (not for use in standing water/oil)
- Engineered to leave no grit behind; safer than other mats that gradually lose their grit -- and their effectiveness -- over time
- 3/8"-thick PVC foam relieves stress on knees, feet, ankles and back from extended standing
- Blend of comfort and traction is ideal for finishing stations, assembly lines and other light work areas
- Rounded edges create a safe transition on and off mat

| Item# | Description | Dimensions | Weight | |
|-------------|-------------|-----------------------|------------|--|
| FLM8504-BK | | 3' W x 5' L x .375" H | 17.25 lbs. | |
| FLM8504-BWY | | 3' W x 5' L x .375" H | 17.25 lbs. | |

Metric Equivalent:

| Item# | Description | Dimensions | Weight |
|-------------|-------------|-------------------------------|--------|
| FLM8504-BK | | 91cm W x 152cm L x 9.5mm H | 7.8 kg |
| FLM8504-BWY | | 91cm W x 152cm L x 9.5mm H | 7.8 kg |

Specifications

| Size | 3' W x 5' L |
|--------------------|-----------------------------|
| Dimensions | 3' W x 5' L x .375" H |
| Chemical Contact | For Light Chemical Splash |
| Oil/Grease Contact | For Light Oil/Grease Splash |
| Anti-Slip | Yes |
| Application | Dry Applications |

| Beveled Edge | Yes |
|------------------------|---|
| Brand | PIG |
| Drainage Holes | Without Holes |
| Grit Surface | Yes |
| Safe for Welding Areas | No |
| Static-Dissipative | No |
| Sold as | 1 each |
| Weight | 17.25 lbs. |
| # per Pallet | 56 |
| Composition | Cushion: PVC Foam Top Coat: Aluminum Oxide and Proprietary Sealant |
| UNSPSC | 52101510 |
| Pigalog® Page Number | Page 231 |

Metric Equivalent

Weight 7.8 kg

Dimensions 91cm W x 152cm L x 9.5mm H

Technical Information

Technical Documents

PIG Anti-Fatigue Mat

Instructions for PIG Anti-Fatigue Matting



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com