



Epoxy Cartridge

FLM857 For PIG Non-Slip Epoxy Tread, Black, Standard Applications

Prevent slips and falls and increase traction on stairs and ramps with a no-drip epoxy cartridge refill for your PIG Non-Slip Epoxy Tread Kit.

- Add slip resistance and create high-traction surfaces to prevent slips and trips at your facility
- Spreadable, no-drip formula cures quickly and is easy to use on sloped surfaces; excellent adhesion and grip to porous and non-porous surfaces like concrete, stone, brick, wood, metal and fiberglass
- Indoor/outdoor, UV-resistant epoxy is more durable, better adhering and longer-lasting than tread tapes and paints
- Black tread color stands out on concrete and most surfaces; can be applied in alternating pattern with other tread colors (sold separately) to maximize visibility
- Withstands exposure to chemicals, weather and extreme temperatures; zero VOC, low odor and USDA Compliant
- Ideal solution for steps, ladder rungs, ramps, wet or oily surfaces, walk-in freezers, loading docks, walkways, locker rooms, boats, pools, curbs and more
- For maximum traction in wet or oily high-traffic areas, add Heavy Duty Tread Grit (sold separately)
- Linear coverage per cartridge varies depending on tread width, application thickness and surface type: 1/2" tread width covers 80–100 linear feet; 1" tread width covers 40–50 linear feet (coverage based on 1/32" epoxy thickness and using forming tape)
- Damaged areas should be repaired before installing; surface should be clean, free of debris and dry before installing
- Mixing Nozzle (FLM864) is required to dispense from the cartridges (sold separately)
- Epoxy bonds are permanent; please refer to instructions before installing

Specifications

Use With

PIG Non-Slip Epoxy Tread

Application

Standard Applications

Application Temperature	45°F (7.2°C) to 95°F (35°C)
Brand	PIG
Handling Time	30 Minutes
Temperature Limit	Works in -20°F (-29°C) to 200°F (93°C)
Color	Black
Volume	400 ml
Sold as	1 each
Weight	1.5 lbs.
# per Pallet	1000
Composition	40% Epoxy Resins 1.5% Catalyst 58.5% Proprietary Ingredient
Shelf Life	2 years
UNSPSC	13111001
Pigalog® Page Number	Page 229

Metric Equivalent

Weight	.7 kg
---------------	-------

Technical Information

StateNoShip

This product is subject to restrictions and cannot be shipped to Alaska or Hawaii.

USOnly

This product can ONLY be shipped to the United States.

Technical Documents

[PIG Non-Slip Epoxy Tread Kit FAQ](#)

[Instructions for PIG Non-Slip Epoxy Tread Kit](#)

[PIG® Non-Slip Epoxy Tread Kit \(Black & Yellow\)](#)



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com