

Ergodyne® Standard Kneeling Mat

FLM960 Standard Applications, Nitrile Rubber Closed Cell Foam, 14" W x 21" L

Protect your knees with cushioned comfort during static kneeling situations by using this kneeling mat with closed-cell foam.

- Thick nitrile rubber (NBR) closed-cell foam keeps its shape over time; won't absorb liquids; non-conductive; resistant to petroleum; silicone-free
- Convenient built-in handle allows for easy transport and hanging storage
- Ideal for mechanics, construction, plumbers, electricians, flooring or anyone looking for comfortable knee support without having to strap on knee pads



Item#	Description	Dimensions	Weight
FLM960-BK		14" W x 21" L x 1" H	1.2 lbs.
FLM960-OR		14" W x 21" L x 1" H	1.2 lbs.

Metric Equivalent:

Item#	Description	Dimensions	Weight
FLM960-BK		36cm W x 53cm L x 2.5cm H	.5 kg
FLM960-OR		36cm W x 53cm L x 2.5cm H	.5 kg

Specifications

Size	14" W x 21" L
Dimensions	14" W x 21" L x 1" H
Chemical Contact	Not for Chemical Contact
Oil/Grease Contact	For Light Oil/Grease Splash
Anti-Slip	No
Application	Standard Applications
Beveled Edge	No
Brand	Ergodyne
Drainage Holes	Without Holes
Grit Surface	No
Safe for Welding Areas	No

Static-Dissipative	No
Sold as	1 each
Weight	1.2 lbs.
Composition	Nitrile Rubber Closed Cell Foam
UNSPSC	52101510

Metric Equivalent

Weight	.5 kg
Dimensions	36cm W x 53cm L x 2.5cm H

Technical Information

USOnly

This product can ONLY be shipped to the United States.



One Pork Avenue • Tipton, PA 16684-0304
1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com