

## Ergodyne® Standard Kneeling Mat

FLM960 Standard Applications, Nitrile Rubber Closed Cell Foam, 14" W x 21" L

Protect your knees with cushioned comfort during static kneeling situations by using this kneeling mat with closed-cell foam.



- Thick nitrile rubber (NBR) closed-cell foam keeps its shape over time; won't absorb liquids; non-conductive; resistant to petroleum; silicone-free
- Convenient built-in handle allows for easy transport and hanging storage
- Ideal for mechanics, construction, plumbers, electricians, flooring or anyone looking for comfortable knee support without having to strap on knee pads

Item#	Description	Dimensions	Weight
FLM960-BK		14" W x 21" L x 1" H	1.2 lbs.
FLM960-OR		14" W x 21" L x 1" H	1.2 lbs.

### Metric Equivalent:

Item#	Description	Dimensions	Weight
FLM960-BK		36cm W x 53cm L x 2.5cm H	.5 kg
FLM960-OR		36cm W x 53cm L x 2.5cm H	.5 kg

### Specifications

Size	14" W x 21" L
Dimensions	14" W x 21" L x 1" H
Chemical Contact	Not for Chemical Contact
Oil/Grease Contact	For Light Oil/Grease Splash
Anti-Slip	No
Application	Standard Applications
Beveled Edge	No
Brand	Ergodyne
Drainage Holes	Without Holes
Grit Surface	No
Safe for Welding Areas	No

**Static-Dissipative**

No

**Sold as**

1 each

**Weight**

1.2 lbs.

**Composition**

Nitrile Rubber Closed Cell Foam

**UNSPSC**

52101510

## Metric Equivalent

**Weight**

.5 kg

**Dimensions**

36cm W x 53cm L x 2.5cm H

## Technical Information

**USOnly**

This product can ONLY be shipped to the United States.



**New Pig**

World's best stuff for leaks, drips and spills.

**One Pork Avenue • Tipton, PA 16684-0304**

1-855-493-4647 • Fax: 1-800-621-7447 • [newpig.com](http://newpig.com) • [hothogs@newpig.com](mailto:hothogs@newpig.com)