

## PIG® Adjustable Frame Storm Drain Filter

FLT006 For Oil; Fuels; Sediment; Floatables, For Storm Drains 20" W x 20" L to 31" W x 31" L, Stainless Steel Adjustable Frame

Finally, a drain insert that won't fall into your catch basin! Innovative design guards your drains with improved filtering of oil, sediment and debris from stormwater runoff.

- Stainless steel adjustable frame adds strength and secures filter in place, so you'll never have to fish out a failed insert again
- Removes oil and holds up to 60 lbs. of sediment, debris and trash; stays in place even when grate is not installed
- Frame easily adjusts by hand to perfectly fit your square or rectangular drains from 20" to 31" W x 20" to 31" L
- Installation, maintenance and removal are now easy, one-person jobs to reduce your labor costs
- Four-stage filtration: PET construction removes contaminants from stormwater at multiple stages, increasing the amount of pollutants captured
- Stormwater flows through drain grate onto fabric shelf (Stage 1), passes over filter ring (Stage 2) into collection bag (Stage 3) and over four sets of filter strips (Stage 4)
- Patented filter ring channels water to center of collection bag to prevent untreated water from escaping through overflow ports
- Filter strips float freely like tentacles to remove hydrocarbons as water moves through collection bag
- Overflow ports help prevent blockage during high water flow
- Heavy-duty straps on all four sides allow easy handling and are visible even with grate in place
- High-visibility straps help inspectors see from a distance that you're proactively managing your stormwater, and serve as a visual reminder for on-site maintenance
- Grommet on bottom of collection bag gives you the option of attaching extra absorbents, filters or other water treatment accessories
- The pore size is 0.074 mm, 74 microns, 0.0029 inches or 200 sieve



## Specifications

<b>Absorbency Range</b>	0 - 0.9 gal.
<b>Style</b>	Inside the Drain
<b>Use With</b>	Storm Drains 20" W x 20" L to 31" W x 31" L
<b>Dimensions</b>	20" W x 20" L x 20" H
<b>Absorbency</b>	Up to .99 gal.
<b>Application</b>	Disposable
<b>Color</b>	Black
<b>Brand</b>	PIG
<b>Drain Shape</b>	Square; Rectangular
<b>Max Flow Rate</b>	317 gal./Minute
<b>Opening Dimensions</b>	12" Dia.
<b>Special Feature</b>	Stainless Steel Adjustable Frame
<b>Substance Filtered</b>	Oil; Fuels; Sediment; Floatables
<b>UV Resistant</b>	Yes
<b>Sold as</b>	1 each
<b>Weight</b>	6.2 lbs.
<b>New Pig Patent</b>	10,508,430
<b># per Pallet</b>	35
<b>Composition</b>	Filter: PET; Absorbent Strips: PET Frame: 304 Stainless Steel Handles: PET
<b>UNSPSC</b>	47101514
<b>Pigalog® Page Number</b>	<a href="#">Page 169</a>

## Metric Equivalent

<b>Absorbency</b>	Up to 3.7 L
<b>Weight</b>	2.8 kg
<b>Dimensions</b>	51cm W x 51cm L x 51cm H

## Technical Information

### Technical Documents

[Instructions for PIG Storm Drain Filter](#)

40 CFR 122.26