



PIG® Adjustable Frame Storm Drain Filter

FLT007 For Oil; Fuels; Sediment; Floatables, For Storm Drains 24" to 37" W & 35" to 49" L, Stainless Steel Adjustable Frame

Finally, a drain insert that won't fall into your catch basin! Innovative design guards your drains with improved filtering of oil, sediment and debris from stormwater runoff.

- Stainless steel adjustable frame adds strength and secures filter in place, so you'll never have to fish out a failed insert again
- Removes oil and holds up to 60 lbs. of sediment, debris and trash; stays in place even when grate is not installed
- Frame easily adjusts by hand to perfectly fit your square or rectangular drains from 24" to 37" W x 35" to 49" L
- Installation, maintenance and removal are now easy, one-person jobs to reduce your labor costs
- Four-stage filtration: PET construction removes contaminants from stormwater at multiple stages, increasing the amount of pollutants captured
- Stormwater flows through drain grate onto fabric shelf (Stage 1), passes over filter ring (Stage 2) into collection bag (Stage 3) and over four sets of filter strips (Stage 4)
- Patented filter ring channels water to center of collection bag to prevent untreated water from escaping through overflow ports
- Filter strips float freely like tentacles to remove hydrocarbons as water moves through collection bag
- Overflow ports help prevent blockage during high water flow
- Heavy-duty straps on all four sides allow easy handling and are visible even with grate in place
- High-visibility straps help inspectors see from a distance that you're proactively managing your stormwater, and serve as a visual reminder for on-site maintenance
- Grommet on bottom of collection bag gives you the option of attaching extra absorbents, filters or other water treatment accessories
- The pore size is 0.074 mm, 74 microns, 0.0029 inches or 200 sieve

Specifications

Absorbency Range	1 - 9.9 gal.
Style	Inside the Drain
Use With	Storm Drains 24" to 37" W & 35" to 49" L
Dimensions	23" W x 34" L x 26" H
Absorbency	Up to 1.25 gal.
Application	Disposable
Color	Black
Brand	PIG
Drain Shape	Square; Rectangular
Max Flow Rate	750 gal./Minute
Opening Dimensions	12" Dia.
Special Feature	Stainless Steel Adjustable Frame
Substance Filtered	Oil; Fuels; Sediment; Floatables
UV Resistant	Yes
Sold as	1 each
Weight	8.4 lbs.
New Pig Patent	10,508,430
# per Pallet	35
Composition	Filter: PET; Absorbent Strips: PET Frame: 304 Stainless Steel Handles: PET
UNSPSC	47101514
Pigalog® Page Number	Page 169

Metric Equivalent

Absorbency	Up to 4.7 L
Weight	3.8 kg
Dimensions	58cm W x 86cm L x 66cm H

Technical Information

Technical Documents

[Instructions for PIG Storm Drain Filter](#)

40 CFR 122.26