



















FLT116 For Oil; Fuels; Sediment; Floatables, For Storm Drains 20" to 30" W & 20" to 36" L; Round Drains 20" to 30" Dia., Trim to Fit

Catch basin insert protects drains of all sizes in high-traffic areas while filtering oil, sediment, debris and trash from stormwater runoff.

- Designed for superior filtration and easy handling
- Frameless design is ideal for small drains of any shape, even shallow drains
- Heavy-duty, high-visibility strap allows easier handling and removal
- Four-stage filtration process treats more water and removes more oil than basic storm drain filters
- Overflow ports help prevent blockage during high water flow
- Affordably priced so you can protect more drains at your facility; no need to pick and choose which ones you can afford to safeguard
- Fits circular drain sizes 20" to 30" in diameter
- Fits irregular, rectangular and square drain sizes 20" to 30" width to 20" to 36" length
- Trim product to allow 3" of material to extend above grate
- Pore size is 0.074 mm, 74 microns, 0.0029 inches or 200 sieve



Specifications

Absorbency Range	1 - 9.9 gal.
Style	Inside the Drain
Use With	Storm Drains 20" to 30" W & 20" to 36" L; Round Drains 20" to 30" Dia.
Dimensions	36" W x 42" L x 17" H
Absorbency	Up to 1.38 gal.
Application	Disposable
Color	Black
Brand	PIG
Drain Shape	Round; Square; Rectangular
Max Flow Rate	500 gal./Minute

Opening Dimensions	10" Dia.
Special Feature	Trim to Fit
Substance Filtered	Oil; Fuels; Sediment; Floatables
UV Resistant	Yes
Sold as	1 each
Weight	1.5 lbs.
Composition	Insert Strips and Ring: PET Straps: PET
UNSPSC	47101514
Pigalog® Page Number	Page 171

Metric Equivalent

Absorbency	Up to 5.2 L
Weight	.7 kg
Dimensions	91cm W x 107cm L x 43cm H

Technical Information

Technical Documents

Instructions for PIG Frameless Storm Drain Filter

40 CFR 122.26



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447• newpig.com • hothogs@newpig.com