


## GutterGuard Curb Inlet Guard

FLT560 For Sediment; Debris, 9" x 10', Max Flow Rate 500 gal./Minute

Block sediment and other debris from curb inlets and storm drains.

- To install, just place in front of curb inlet, with no weights or hardware required
- Keeps silt and debris out of curb-style storm drains
- During heavy rain, overflow ports prevent ponding in front of drain
- Reusable design can be cleaned and stored for less waste, expense and maintenance than other drain protection methods
- Useful as a best management practice in stormwater pollution prevention plans
- Ideal for construction sites, municipal streets, parking lots, etc



### Specifications

<b>Style</b>	Around the Drain
<b>Use With</b>	Curb Opening up to 8'
<b>Dimensions</b>	ext. dia. 9" x 10' L
<b>Recycled Content</b>	100% Post-Consumer Recycled Polypropylene Fibers
<b>Brand</b>	Ultratech GutterGuard
<b>Drain Shape</b>	Rectangular
<b>Color</b>	Gray/Yellow
<b>Max Flow Rate</b>	500 gal./Minute
<b>Substance Filtered</b>	Sediment; Debris
<b>UV Resistant</b>	Yes
<b>Distributor Part Number</b>	4355372;04088x89867
<b>Sold as</b>	1 each
<b>Weight</b>	24 lbs.
<b># per Pallet</b>	10
<b>Composition</b>	Filter Skin - Polyethylene (HDPE) Mesh

Rolled Media - Synthetic Fiber

UNSPSC

47101514

Pigalog® Page Number

Page 175

## Metric Equivalent

Dimensions

ext. dia. 22.9cm x 3m L

Weight

10.9 kg

## Technical Information

### Technical Documents

40 CFR 122.26



**New Pig**

World's best stuff for leaks, drips and spills.

**One Pork Avenue • Tipton, PA 16684-0304**

1-855-493-4647 • Fax: 1-800-621-7447 • [newpig.com](http://newpig.com) • [hothogs@newpig.com](mailto:hothogs@newpig.com)