DeWatering Bag

FLT562 For Up to 6" Dia. Discharge Hose,Max Flow Rate 500 gal./Minute,6' W x 6' L

Remove oil, sediment and pollutants from high volume pump outs.

- Ideal for spill cleanup, draining during construction or pumping out containment areas, sumps and ponds
- Extra-large bag has greater capacity for extensive dewatering operations
- Accommodates up to a 6" discharge hose for high volume pumping
- Disperses water to help prevent erosion
- Non-biodegradable skin has low ash and high BTU value
- Landfillable or incinerable for waste reduction/fuels blending

Specifications

Absorbency Range	1 - 9.9 gal.
Style	Beyond the Drain
Use With	Up to 6" Dia. Discharge Hose
Dimensions	6' W x 6' L
Recycled Content	100% Post-Consumer Recycled Textiles
Absorbency	Up to 3.7 gal.
Color	Black
Brand	Ultratech
Capacity	36 cu. ft.
Max Flow Rate	500 gal./Minute
Micron Rating	180 Microns
Separator Type	Dewatering & Silt Bags & Socks
Substance Filtered	Oil; Fuels; Sediment; Floatables
Sold as	1 each

Weight	5.4 lbs.
Composition	Non-Woven Polyethylene
UNSPSC	47101525
Pigalog® Page Number	Page 178

Metric Equivalent

Absorbency	Up to 14 L
Weight	2.4 kg
Dimensions	183cm W x 183cm L

Technical Information

Technical Documents

Why is there no SDS?

40 CFR 122.26

New Pig
World's best stuff for leaks, drips and spills.

One Pork Avenue • Tipton, PA 16684-0304
1-855-493-4647 • Fax: 1-800-621-7447• newpig.com • hothogs@newpig.com