



PipeSock

FLT564 For Up to 8" Dia. Pipes, Max Flow Rate 106 gal./Minute, 8" x 5'

PipeSock fits 8" dia. pipes to help you control and contain oil and sediment during dewatering and pump-outs of sumps and collection ponds.

- Ideal for pumping out containment areas, collection ponds, utility vaults and sumps
- Simply attach to hose or pipe to remove hydrocarbons and sediment from pumped water
- Ultra-Filter-Tex recycled fibers provide high efficiency and excellent flow
- Attaches easily to pipes and hoses with a simple pipe clamp or heavy zip tie (not included)
- Incinerable and fuels-blendable with high Btu value and low ash



Specifications

Absorbency Range	0 - 0.9 gal.
Style	Beyond the Drain
Use With	Up to 8" Dia. Pipes
Dimensions	ext. dia. 8" x 5' L
Recycled Content	100% Post-Consumer Recycled Synthetic Fibers
Absorbency	Up to .81 gal.
Color	Black
Brand	Ultratech
Capacity	1.7 cu. ft.
Max Flow Rate	106 gal./Minute
Micron Rating	150 Microns
Separator Type	Dewatering & Silt Bags & Socks
Substance Filtered	Oil; Sediment
Thickness	115.5 mil

Sold as	1 each
Weight	2 lbs.
Composition	Ultra-Filter-TEX Fibers
Includes	1 - Pipe Sock 1 - 60" H x 36" W Disposal Bag
UNSPSC	47101525
Pigalog® Page Number	<u>Page 176</u>

Metric Equivalent

Absorbency	Up to 3.1 L
Weight	.9 kg
Dimensions	ext. dia. 20cm x 152cm L

Technical Information

Technical Documents

Why is there no SDS?

40 CFR 122.26



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com