



PIG® Frameless Storm Drain Filter

FLT615 For Fuels; Oil; Sediment; Debris, For Storm Drains 24" to 48" W & 24" to 54" L; Round Drains 24" to 48" Dia., Trim to Fit

Catch basin insert protects drains of all sizes in high-traffic areas while filtering oil, sediment, debris and trash from stormwater runoff.

- Designed for superior filtration *and* easy handling
- Frameless design is ideal for small drains of any shape, even shallow drains
- Heavy-duty, high-visibility strap allows easier handling and removal
- Four-stage filtration process treats more water and removes more oil than basic storm drain filters
- Overflow ports help prevent blockage during high water flow
- Affordably priced so you can protect more drains at your facility; no need to pick and choose which ones you can afford to safeguard
- Fits circular drain sizes 24" to 48" in diameter
- Fits irregular, rectangular and square drain sizes 24" to 48" width to 24" to 54" length
- Trim product to allow 3" of material to extend above grate
- Pore size is 0.074 mm, 74 microns, 0.0029 inches or 200 sieve



Specifications

Style	Inside the Drain
Use With	Storm Drains 24" to 48" W & 24" to 54" L; Round Drains 24" to 48" Dia.
Dimensions	54" W x 60" L x 17" H
Absorbency	Up to 2.06 gal.
Application	Disposable
Brand	PIG
Color	Black
Drain Shape	Round; Square; Rectangular
Max Flow Rate	500 gal./Minute
Opening Dimensions	10" Dia.

Special Feature	Trim to Fit
Substance Filtered	Fuels; Oil; Sediment; Debris
UV Resistant	Yes
Sold as	1 each
Weight	2.5 lbs.
# per Pallet	80
Composition	Insert: PET Absorbent Strips: PET Ring: PET Straps: PET
UNSPSC	47101514
Pigalog® Page Number	<u>Page 171</u>

Metric Equivalent

Absorbency	Up to 7.8 L
Weight	1.1 kg
Dimensions	137cm W x 152cm L x 43cm H

Technical Information

Technical Documents

Instructions for PIG Frameless Storm Drain Filter

40 CFR 122.26



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com