

DeWatering Bag

FLT617 For Oil; Sediment, For Up to a 6" Dia. Discharge Hose, Max Flow Rate 1500 gal./Minute



Remove oil, sediment and pollutants from high volume pump outs.

- Ideal for spill cleanup, draining during construction or pumping out containment areas, sumps and ponds
- Extra-large bag has greater capacity for extensive dewatering operations
- Accommodates up to a 6" discharge hose for high volume pumping
- Disperses water to help prevent erosion
- Non-biodegradable skin has low ash and high BTU value
- Landfillable or incinerable for waste reduction/fuels blending



Specifications

| | |
|--------------------------------|--------------------------------------|
| Style | Beyond the Drain |
| Use With | Up to a 6" Dia. Discharge Hose |
| Dimensions | 15' W x 15' L |
| Recycled Content | 100% Post-Consumer Recycled Textiles |
| Absorbency | Up to 22.6 gal. |
| Brand | Ultratech |
| Color | Black |
| Capacity | 225 cu. ft. |
| Max Flow Rate | 1500 gal./Minute |
| Micron Rating | 180 Microns |
| Separator Type | Dewatering & Silt Bags & Socks |
| Substance Filtered | Oil; Sediment |
| Distributor Part Number | 3733486;04088x89866 |
| Sold as | 1 each |
| Weight | 28 lbs. |
| # per Pallet | 16 |
| Composition | Non-Woven Polypropylene |
| UNSPSC | 47101525 |
| Pigalog® Page Number | Page 182 |

Metric Equivalent

| | |
|-------------------|--------------|
| Absorbency | Up to 85.5 L |
|-------------------|--------------|

| | |
|-------------------|-----------------|
| Dimensions | 4.6m W x 4.6m L |
|-------------------|-----------------|

| | |
|---------------|---------|
| Weight | 12.7 kg |
|---------------|---------|

Technical Information

Technical Documents

Why is there no SDS?

40 CFR 122.26



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com