

Storm Sentinel® Round Drain Protection Insert

FLT704 For Sediment; Debris; Trash, For Round Drains 27" to 29" Dia., Wire Structural Frame

Heavy-gauge collars keep insert below the grate and above the catch basin, even when loaded with 135 lb. of sediment.



- Below-grate design presents no trip hazard and stays intact in areas with high vehicle traffic
- Rugged 8-ounce polypropylene geotextile withstands weather and abrasion for long life
- Heavy-gauge, sewn-in wire collar forms structural frame that rests on drain perimeter to keep insert from falling in when grate is removed
- Pocket collects up to 135 lb. of wet sediment, trash and debris while allowing water flow up to 500 gpm
- Features three excess flow ports to prevent blockage during high water flow
- Durable loop handle helps make removal quick and easy
- Ideal as a Best Management Practice when included in your Stormwater Pollution Prevention Plan



Specifications

Style	Inside the Drain
Use With	Round Drains 27" to 29" Dia.
Application	Disposable
Brand	ENPAC
Drain Shape	Round
Max Flow Rate	500 gal./Minute
Color	Black
Opening Dimensions	Adjustable from 27" to 29" Dia.
Special Feature	Wire Structural Frame
Substance Filtered	Sediment; Debris; Trash
UV Resistant	Yes
Distributor Part Number	4415118;04088x69996
Sold as	1 each

Weight	2 lbs.
# per Pallet	6
Composition	Polypropylene
UNSPSC	47101514

Metric Equivalent

Weight	.9 kg
---------------	-------

Technical Information

Technical Documents

40 CFR 122.26



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com