

## Filtrexx® FilterSoxx with PetroLoxx™

FLT711 For Oil; Sediment; Debris, 5" x 10', Max Flow Rate 2 gal./Minute



Protect storm drains from pollutants including sediment, debris, hydrocarbons and chemicals.

- Organic compost/mulch filler achieves a 97.2% total solid removal
- Also efficiently filters oils, diesel, gasoline and hydrocarbon sheens from stormwater
- Barrier provides effective erosion and sedimentation control with constant-flow filtration at 2 gpm/linear foot
- Easy to handle and move as needed
- Ideal for uses where mobility matters, such as site entrances and exits
- Installs easily on nearly any surface, even pavement or frozen ground
- Product's own weight holds it in place, eliminating need for stakes or extra equipment
- Minimize replacement costs by surrounding any size drain with any quantity, rotating and swapping out when saturated as needed
- Won't rip, tear or fall down like silt fencing
- Bio-based, organic materials help you meet environmental goals
- PetroLoxx additive filters oils, diesel, gasoline and hydrocarbon sheens from stormwater; more effective than straw wattles, which only stop erosion
- Strong double-polyester skin blocks sediment and withstands demands such as vehicle traffic
- Ideal for use in salvage yards, landfills and recycling centers



Filtrexx



### Specifications

Max Flow Rate	2 gal./Minute
Use With	Storm Drains, Culverts, and Ditches
Color	Black
Dimensions	ext. dia. 5" x 10' L
Recycled Content	95% Pre-Consumer Recycled Cellulose
Absorbency	Up to 4.5 gal.
Brand	Filtrexx

<b>Substance Filtered</b>	Oil; Sediment; Debris
<b>Sold as</b>	1 each
<b>Weight</b>	30 lbs.
<b># per Pallet</b>	40
<b>Composition</b>	Skin - Polyester Filler - Compost Mulch
<b>UNSPSC</b>	47101514
<b>UV Resistant</b>	Yes
<b>Metric Equivalent</b>	
<b>Absorbency</b>	Up to 17 L
<b>Dimensions</b>	ext. dia. 12.7cm x 3m L
<b>Weight</b>	13.6 kg

## Technical Information

### Technical Documents

Why is there no SDS?

40 CFR 122.26



**One Pork Avenue • Tipton, PA 16684-0304**

1-855-493-4647 • Fax: 1-800-621-7447 • [newpig.com](http://newpig.com) • [hothogs@newpig.com](mailto:hothogs@newpig.com)