

Filtrexx® FilterPillow with PetroLoxx™

FLT714 For Oil; Sediment; Debris, 19" x 28", Max Flow Rate 2 gal./Minute

Protect storm drains from pollutants including sediment, debris, hydrocarbons and chemicals.

- Organic compost/mulch filler achieves a 97.2% total solid removal
- Also efficiently filters oils, diesel, gasoline and hydrocarbon sheens from stormwater
- Barrier provides effective erosion and sedimentation control with constant-flow filtration at 2 gpm/linear foot
- Easy to handle and move as needed
- Ideal for uses where mobility matters, such as site entrances and exits
- Installs easily on nearly any surface, even pavement or frozen ground
- Product's own weight holds it in place, eliminating need for stakes or extra equipment
- Minimize replacement costs by surrounding any size drain with any quantity, rotating and swapping out when saturated as needed
- Won't rip, tear or fall down like silt fencing
- Bio-based, organic materials help you meet environmental goals
- Strong HDPE woven geotextile skin blocks sedimentation and withstands demanding environments
- PetroLoxx additive filters oils, diesel, gasoline and hydrocarbon sheens from stormwater



Filtrexx

Specifications

Style	Around the Drain
Use With	Storm Drains, Culverts, and Ditches
Dimensions	19" W x 28" L
Absorbency	Up to 10.5 gal. per bag
Brand	Filtrexx
Drain Shape	Round; Square; Rectangular
Color	Orange
Max Flow Rate	2 gal./Minute
Substance Filtered	Oil; Sediment; Debris

UV Resistant	Yes
Distributor Part Number	4802305;04088x00203
Sold as	3 pillows per bag
Weight	37.65 lbs.
# per Pallet	28
Composition	Skin - Polyester Filler - Compost Mulch
UNSPSC	47101514

Metric Equivalent

Absorbency	Up to 39.7 L per bag
Dimensions	48.3cm W x 71.1cm L
Weight	17.1 kg

Technical Information

Technical Documents

Why is there no SDS?

40 CFR 122.26



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com