









FLT730 For Oil, Each absorbs up to 5 gal., Max Flow Rate 1 gal./Minute

Self-contained unit connects to a Leak Diverter to trap oils and help you comply with SPCC and stormwater regulations.

- Oil-only absorbents packed into bucket soak up hydrocarbons but repel water, which passes over the absorbents and flows through the bucket to the lower drainage point
- Seven alternating layers of Oil-Only Mat Pads and Oil-Only Pillows offer high oil retention for fewer changeouts
- Hose fitting on top of container lid accepts 3/4" drainage hose from a Leak Diverter or other liquid sources; bucket can be located almost anywhere
- Container and absorbents are both UV resistant for long-term outdoor use without degradation
- 3/4" connection on bottom of container accepts a self bailer, drain plug (included), drainage hose (also included) or can be used as a freeflowing drain
- 20-gallon container holds oil-absorbent media to remove up to 5 gallons of oil, grease and hydrocarbons without taking in a drop of water





Specifications

Style	Oil, Water Separator
Dimensions	ext. dia. 22.5" x 18.88" H
Absorbency	Up to 5 gal.
Brand	PIG
Drain	.75" NPT
Max Flow Rate	1 gal./Minute
Color	Yellow
Substance Filtered	Oil
Distributor Part Number	6035155;04088x00459
Sold as	1 each
Weight	30 lbs.
New Pig Patent	Patent Pending

# per Pallet	12
Composition	Bucket - Polyethylene Filter Media - Polypropylene Hose - PVC Plug - Polyethylene (HDPE)
Includes	 1 - Bucket w/Lid & Fittings 4 - 18" dia. PIG® Brown Oil-Only Mat Pads 3 - 24" W x 25" L PIG® Oil-Only Pillows 1 - 6' Hose 1 - Plug
UNSPSC	47101514
Pigalog® Page Number	Page 50

Metric Equivalent

Absorbency	Up to 18.9 L
Dimensions	ext. dia. 57.2cm x 48cm H
Weight	13.6 kg

Technical Information

Technical Documents

Instructions for PIG Filter Bucket Refill

PIG® Oil-Only Absorbents

40 CFR 122.26



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447• newpig.com • hothogs@newpig.com