



PIG® Stormwater Filter Sock

FLT821 For Oil; Sediment; Debris; Trash, 12.75" x 10' x 3", Max Flow Rate 20 gal./Minute

Remove oil, trash and debris from stormwater runoff with our innovative dual-chamber sock.

- Highly absorbent proprietary filler pulls in oil and pollutants from stormwater runoff; lets clean water pass through
- Stays in place without staking or trenching
- Durable geotextile skin removes total suspended solids (TSS) over 297 microns (50 mesh) and maintains an impressive flow rate of 2 gpm per foot
- Flexible design follows the contours of uneven ground for maximum surface contact; can be shaped to create fully contained spaces
- Heavy-duty straps make filter socks easy to carry while you install, reposition or replace socks
- Protect more than your drains! Also ideal for source pollutant removal around dumpsters, oil containment areas, roof drains, property perimeters, outfall pipes, downspouts and stockpiles



Specifications

Style	Around the Drain
Use With	Storm Drains, Culverts, Stockpile Perimeter, Dumpster Perimeter, Roof Drains, Downspouts and Trench Drains
Dimensions	12.75" W x 10' L x 3" H
Recycled Content	85% Post-Consumer Recycled Synthetic Fibers
Absorbency	Up to 4.5 gal.
Brand	PIG
Color	Blue
Drain Shape	Round; Square; Rectangular
Max Flow Rate	20 gal./Minute
Substance Filtered	Oil; Sediment; Debris; Trash
UV Resistant	Yes
Distributor Part Number	494k86
Sold as	1 each

Weight	44 lbs.
New Pig Patent	10,865,126
# per Pallet	20
Composition	Skin: Polypropylene Geotextile High Visibility Handles: Nylon Oil Removal Chamber: Recycled Fiber Mat Weighted Chamber: Stone Aggregate
UNSPSC	47101514
Pigalog® Page Number	<u>Page 180</u>

Metric Equivalent

Absorbency	Up to 17 L
Dimensions	32.4cm W x 3m L x 7.6cm H
Weight	20 kg

Technical Information

Technical Documents

Instructions for PIG Stormwater Filter Sock

PIG® Stormwater Filter Sock

40 CFR 122.26



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com