



## **PIG® Over-The-Drain Sediment Filter**

FLT830 For Sediment; Floatables, For Storm Drains  
24" W x 24" L, Magnetic Strips

Our magnetic over the drain inlet filter installs effortlessly to remove sediment and debris from stormwater runoff, even during high-flow events.

- Remove sediment and debris from stormwater before it enters your drains and inlets; ideal as a Best Management Practice (BMP) to help avoid violations
- Integrated magnetic strips on underside of filter allow easy installation in seconds; just set it in place — no lifting grate, no cable ties, no pinched fingers
- Natural coconut fibers are densely woven and vertically oriented to maximize sediment removal and flow rate
- Designed and tested to remove 99% of particulate size 0.425mm and larger
- Built-in ports and scalloped edges help resist clogging; removable plugs offer overflow protection during high-flow storm events
- For curb-style inlets without a grate, filter can be folded in half and "stuffed" into opening; friction fit holds filter in place
- Reusable product can be washed and reinstalled for extended service



## Specifications

Style	Over the Drain
Use With	Storm Drains 24" W x 24" L
Dimensions	30" W x 30" L x 2.25" H
Application	Reusable
Brand	PIG
Drain Shape	Square
Color	Blue
Max Flow Rate	650 gal./Minute
Special Feature	Magnetic Strips
Substance Filtered	Sediment; Floatables
Thickness	2.25"

<b>UV Resistant</b>	Yes
<b>Sold as</b>	1 each
<b>Weight</b>	7.44 lbs.
<b># per Pallet</b>	15
<b>Composition</b>	Natural Renewable Coconut Fiber
<b>UNSPSC</b>	47101514
<b>Pigalog® Page Number</b>	<u>Page 173</u>

## Metric Equivalent

<b>Weight</b>	3.4 kg
<b>Dimensions</b>	76cm W x 76cm L x 5.7cm H

## Technical Information

### Technical Documents

Instructions for PIG Over-The-Drain Sediment Filter

40 CFR 122.26



**One Pork Avenue • Tipton, PA 16684-0304**

1-855-493-4647 • Fax: 1-800-621-7447 • [newpig.com](http://newpig.com) • [hothogs@newpig.com](mailto:hothogs@newpig.com)