

## Oil Safe® Premium Pump

GEN172 For Oil Safe Container, 5' L Discharge Hose

Add this versatile pump to your Oil Safe® system for reliable lubrication.



- Pump screws into Utility Lid (sold separately) on 3 qt., 5 qt and 10 qt. Oil Safe® Containers to dispense lubricants in hard-to-reach spots
- Angled nozzle cleanly and accurately dispenses 3 oz. per stroke
- Flexible hose has inner coiled wire to resist kinking
- Features port for filling with pump in place
- Fill port also holds nozzle between jobs to prevent drips
- Nylon pump with Viton® O-rings is compatible with ISO 680 viscosity oils and lubricants, including synthetics, for years of reliable performance
- Non-return discharge valve reduces backpressure to improve pumping efficiency
- Quick-release body collar allows access to internal parts for easy maintenance
- Notched tube let uninterrupted flow reach container bottom, and tube sleeve can extend to accommodate deeper 10-qt. containers
- Comfortable D-handle grip

Item#	Description	Dimensions	Weight
GEN172-BK			3 lbs.
GEN172-BL			3 lbs.
GEN172-DG			3 lbs.
GEN172-GR			3 lbs.
GEN172-GY			3 lbs.
GEN172-OR			3 lbs.
GEN172-PR			3 lbs.
GEN172-RD			3 lbs.
GEN172-TN			3 lbs.
GEN172-YW			3 lbs.

### Metric Equivalent:

Item#	Description	Dimensions	Weight
GEN172-BK			1.4 kg

GEN172-BL	1.4 kg
GEN172-DG	1.4 kg
GEN172-GR	1.4 kg
GEN172-GY	1.4 kg
GEN172-OR	1.4 kg
GEN172-PR	1.4 kg
GEN172-RD	1.4 kg
GEN172-TN	1.4 kg
GEN172-YW	1.4 kg

## Specifications

<b>Use With</b>	Oil Safe Container
<b>Brand</b>	Oil Safe
<b>Discharge Hose</b>	5' L
<b>Sold as</b>	1 each
<b>Weight</b>	3 lbs.
<b>Composition</b>	Pump: Nylon O-Rings: Viton Hose: PVC
<b>UNSPSC</b>	40151524
<b>Pigalog® Page Number</b>	<u><a href="#">Page 340</a></u>

## Metric Equivalent

<b>Weight</b>	1.4 kg
---------------	--------

## Technical Information



**One Pork Avenue • Tipton, PA 16684-0304**

1-855-493-4647 • Fax: 1-800-621-7447 • [newpig.com](http://newpig.com) • [hothogs@newpig.com](mailto:hothogs@newpig.com)