

PIG™ Deluxe Pipe Patch Kit

GEN313 Pressurized, For .5" - 5" dia.

Stainless steel clamps and tight-sealing neoprene liners quickly stop pressurized pipe leaks.

- Stainless steel pipe clamps and tight-sealing neoprene liners quickly stop pressurized pipe leaks
- Clamps work on odd-size pipes and out-of-round pipes 1/2" to 5" in diameter
- 150 PSI max pressure for 1/2" to 4" clamps; 100 PSI max pressure for 5" clamps
- Included ratchet wrench speeds repairs
- Makes jobs easier with extra supplies including PIG® Repair Putty and PIG® Mat
- Packaged in a plastic hardshell case for easy transport



Specifications

Color	Black
Brand	PIG
Pipe Size	.5" - 5" dia.
Pipe Pressure	Pressurized
Temperature Limit	180°F (82°C)
Sold as	1 each
Weight	29 lbs.
# per Pallet	20
Composition	Clamps - Stainless Steel Clamp Liners - Neoprene

Includes

- 1 - Carrying Case
- 1 - Ratchet Box Wrench
- 1 - 1/2" x 3" Repair Clamp
- 1 - 3/4" x 3" Repair Clamp
- 1 - 3" x 6" Repair Clamp
- 1 - 1" x 3" Repair Clamp
- 1 - 3 1/2" x 6" Repair Clamp
- 1 - 1 1/4" x 6" Repair Clamp
- 1 - 4" x 6" Repair Clamp
- 1 - 1 1/2" x 6" Repair Clamp
- 1 - 5" x 6" Repair Clamp
- 1 - 2" x 6" Repair Clamp
- 1 - 2 1/2" x 6" Repair Clamp

1 - 9" x 9" x 1/8" Neoprene Patch
5 - 15" x 20" PIG® Universal Mat Pads (MAT203)
2 - PIG® Multi-Purpose Repair Putty Sticks (PTY201)

Pieces	21 Pieces
Shelf Life	2 years
UNSPSC	27113201
Pigalog® Page Number	<u>Page 275</u>

Metric Equivalent

Weight	13.2 kg
---------------	---------

Technical Information

CountryNoShip

This product is subject to export restrictions and cannot be shipped to Canada or the European Union.

Technical Documents

[Instructions for Using PIG Deluxe Pipe Patch Kit](#)

[PIG® Multi-Purpose Repair Putty](#)



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com