

## QRP® Qualatherm® Heat & Cold Resistant Gloves



GLV1002 Lining Nylon; Wool, Coating None, 1 pair per package

Protect hands from extreme temperatures while protecting electronics from static by wearing these ESD gloves made to handle dry contact temperatures from -210 to 1400 degrees Fahrenheit.

- Made to handle dry contact with temperatures from -210 to 1400 degrees Fahrenheit with no charring, ash or residue
- Reusable with an ambidextrous pattern to help reduce wear and costs
- PBI outer shell and nylon/wool lining
- No PCB, asbestos or fiberglass
- ESD protection up to  $10^9$  ohms
- ESD-safe compliance to ANSI/ESD S20.20-2014
- Ideal for use in a variety of applications including diffusion furnaces, quartz wafer boats, liquid gas flask handling (ultra cold) and hot/dry glassware handling



Item#	Description	Dimensions	Weight
GLV1002-M	Medium	14" L	1 lb.
GLV1002-L	Large	14" L	1 lb.
GLV1002-XL	X-Large	14" L	1 lb.

### Metric Equivalent:

Item#	Description	Dimensions	Weight
GLV1002-M	Medium	36cm L	.5 kg
GLV1002-L	Large	36cm L	.5 kg
GLV1002-XL	X-Large	36cm L	.5 kg

### Specifications

<b>Style</b>	Extreme-Temperature
<b>Dimensions</b>	14" L
<b>Brand</b>	PIP
<b>Coating</b>	None

<b>Cuff</b>	Hemmed
<b>Lining</b>	Nylon; Wool
<b>Color</b>	Brown
<b>Primary Material</b>	PBI
<b>Texture</b>	None
<b>Sold as</b>	1 pair per package
<b>Weight</b>	1 lb.
<b>Composition</b>	PBI
<b>UNSPSC</b>	46181504

## Metric Equivalent

<b>Weight</b>	.5 kg
<b>Dimensions</b>	36cm L

## Technical Information

**USOnly**

This product can ONLY be shipped to the United States.

## Certifications, Approvals and Ratings

ANSI / ISEA 105-2016,ANSI/ESD S20.20

## Technical Documents

29 CFR 1910.132

29 CFR 1910.138



**One Pork Avenue • Tipton, PA 16684-0304**

1-855-493-4647 • Fax: 1-800-621-7447 • [newpig.com](http://newpig.com) • [hothogs@newpig.com](mailto:hothogs@newpig.com)