

QRP® Qualatril® Disposable Nitrile Cleanroom Finger Cots



GLV1005 Powder-Free, Thickness 3.5 mil, 720 per package

Protect your electronics from electrostatic discharge by wearing these Class II ESD, latex-free nitrile finger cots, even in your cleanroom.

- For use with Class II static sensitive devices (thresholds above 1000 V)
- Average surface resistance of 5×10^9 ohms per square unit
- ESD-safe compliance to ANSI/ESD S20.20-2014
- Packaged for ISO 5 (Class 100) applications
- Ideal for keeping in ESD-sensitive areas, repair stations and assembly areas, with uses across avionics, defense, marine electronics, consumer electronics and IC industries, including wire bonding and more
- Unique stand-up pouch packaging for easy product identification



Item#	Description	Dimensions	Weight
GLV1005-S	Small	2.75" L	.8 lbs.
GLV1005-M	Medium	2.75" L	.8 lbs.
GLV1005-L	Large	2.75" L	.8 lbs.
GLV1005-XL	X-Large	2.75" L	.8 lbs.

Metric Equivalent:

Item#	Description	Dimensions	Weight
GLV1005-S	Small	7cm L	.4 kg
GLV1005-M	Medium	7cm L	.4 kg
GLV1005-L	Large	7cm L	.4 kg
GLV1005-XL	X-Large	7cm L	.4 kg

Specifications

ISO Cleanroom Classification	5
Style	Chemical-Resistant
Dimensions	2.75" L
Brand	PIP

Cuff	Straight
Grade	Cleanroom
Color	White
Powdered	Powder-Free
Primary Material	Nitrile
Thickness	3.5 mil
Texture	Smooth
Sold as	720 per package
Weight	.8 lbs.
Composition	Nitrile
UNSPSC	46181504

Metric Equivalent

Weight	.4 kg
Dimensions	7cm L

Technical Information

USOnly

This product can ONLY be shipped to the United States.

Certifications, Approvals and Ratings

Cleanroom Class 100,ANSI/ESD S20.20

Technical Documents

[29 CFR 1910.132](#)

[29 CFR 1910.138](#)



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com