

Ergodyne® Proflex® A4 Nitrile Coated Cut-Resistant Gloves

GLV1220 Level 4, Coating Nitrile, 1 pair

Protect your hands from light-to-moderate cut risks while retaining functional dexterity in these 13-gauge Ergodyne ProFlex cut-resistant gloves.

- 13-gauge ANSI A4 cut-resistant gloves stop light-to-moderate cuts, punctures and abrasions; ASTM F2992 cut tested and approved.
- Ergodyne's ProFlex material enables you to keep using your hands with dexterity in these touchscreen gloves.
- Ideal for metal fabrication and appliance manufacturing to drywall work, carpet installation and more.
- Versatile WSX-dip dual-layer technology gives you comfort, safety and performance.
- Anti-slip nitrile outer layer grips securely even in wet or oily conditions.
- Polyurethane underlayer wicks sweat and brings in cooling air flow; TenaLux yarn breathes and prevents irritation without compromising protection.
- Long, seamless knit cuffs help keep out dirt.
- High-visibility color adds safety around machines and co-workers.
- Conveniently machine washable.



| Item# | Description | Dimensions | Weight |
|-------------|-------------|------------|----------|
| GLV1220-S | Small | 9.5" L | .19 lbs. |
| GLV1220-M | Medium | 9.5" L | .19 lbs. |
| GLV1220-L | Large | 9.5" L | .19 lbs. |
| GLV1220-XL | X-Large | 9.5" L | .19 lbs. |
| GLV1220-XXL | XX-Large | 9.5" L | .19 lbs. |

Metric Equivalent:

| Item# | Description | Dimensions | Weight |
|-----------|-------------|------------|--------|
| GLV1220-S | Small | 24cm L | 86 g |
| GLV1220-M | Medium | 24cm L | 86 g |
| GLV1220-L | Large | 24cm L | 86 g |

| | | | |
|-------------|----------|--------|------|
| GLV1220-XL | X-Large | 24cm L | 86 g |
| GLV1220-XXL | XX-Large | 24cm L | 86 g |

Specifications

| | |
|-----------------------------|---|
| Style | Cut-Resistant |
| Dimensions | 9.5" L |
| Brand | Ergodyne |
| Coating | Nitrile |
| Cuff | Extended |
| Cut-Resistant Level | 4 |
| Lining | None |
| Primary Material | Polyethylene |
| Texture | Textured |
| Thickness | 13 gauge |
| Sold as | 1 pair |
| Weight | .19 lbs. |
| # per Pallet | 4800 |
| Composition | High-performance polyethylene (HPPE) Polyurethane Nitrile |
| UNSPSC | 46181504 |
| Pigalog® Page Number | <u>Page N19</u> |

Metric Equivalent

| | |
|-------------------|--------|
| Dimensions | 24cm L |
| Weight | 86 g |

Technical Information

| |
|--|
| Certifications, Approvals and Ratings |
| EN 388 Cut Level 4,ANSI / ISEA 105-2016 |
| USOnly |

This product can ONLY be shipped to the United States.

Technical Documents

[29 CFR 1910.132](#)

[29 CFR 1910.138](#)

