

## G-Tek® VR-X™ Polyurethane Coated Gloves



GLV651 Coating Polyurethane, Lining Nylon, 12 pair per package

Assemble small parts and handle other precision tasks in these high-dexterity gloves that meet a wide range of testing standards.

- Ideal for handling and assembly of small-to-medium parts and materials as well as manufacturing, inspection, shipping/packaging and mechanical equipment maintenance/repair
- VR-X polyurethane coating provides advanced barrier protection
- Precise handling: treated coating takes on surface properties of liner for a tactile grip in wet, dry and slightly oily conditions
- Nylon-blended shell with ultra-thin 18 gauge liner adds to exceptional dexterity
- Touchscreen compatible: operate a touchscreen phone or device without removing gloves
- Knit wrist helps prevent dirt and debris from entering the glove
- Washable
- Resistant to water and UV light
- Anti-viral barrier protection per ISO 20743:2013 test method and EN374-5
- Liquid proof, air-leak tested - EN374-2
- ESD Safe; Surface Resistance per ESD S11.11 Static Dissipative Range at  $10^8$  ohms, 12 percent RH, 48 hours at 100 V
- 4.0 AQL
- ASTM D6978 Chemotherapy Drug Tested; protection against fentanyl



Item#	Description	Dimensions	Weight
GLV651-XS	X-Small	12" L	1.2 lbs.
GLV651-S	Small	12" L	1.2 lbs.
GLV651-M	Medium	12" L	1.2 lbs.
GLV651-L	Large	12" L	1.2 lbs.
GLV651-XL	X-Large	12" L	1.2 lbs.
GLV651-XXL	XX-Large	12" L	1.2 lbs.

## Metric Equivalent:

Item#	Description	Dimensions	Weight
GLV651-XS	X-Small	30cm L	.5 kg
GLV651-S	Small	30cm L	.5 kg
GLV651-M	Medium	30cm L	.5 kg
GLV651-L	Large	30cm L	.5 kg
GLV651-XL	X-Large	30cm L	.5 kg
GLV651-XXL	XX-Large	30cm L	.5 kg

## Specifications

Dimensions	12" L
Brand	PIP
Coating	Polyurethane
Cuff	Knit
Lining	Nylon
Primary Material	Nylon
Color	Black/Blue
Texture	Foam
Sold as	12 pair per package
Weight	1.2 lbs.
Composition	Liner: Nylon Coating: Polyurethane
UNSPSC	46181504

## Metric Equivalent

Weight	.5 kg
Dimensions	30cm L

## Technical Information

### US Only

This product can ONLY be shipped to the United States.

### Certifications, Approvals and Ratings

ANSI/ISEA105-2016 PUNCTURE 2,EN388:2016,EN374-5:2016,EN374-2,ASTM D6978-05 (2019) Fentanyl Testing

### Technical Documents

[29 CFR 1910.132](#)

[29 CFR 1910.138](#)