

## FTI .33 HP Electric IBC Pump System with EFP Pick-Up Tube

IBC8002 For Thin-Bodied & Slightly Viscous Liquids in Non-Explosive Areas, Max Flow Rate 10 gal./Minute, For 275 gal. IBC w/ 2" NPT Bung

Batch dispense mild corrosives, cleaners and lab chemicals with this economical, dual speed IBC tote pump system for use with 275-gallon IBC totes.

- Light-weight, easy-to-handle .33 HP electric pump motor with dual speed toggle switch provides better flow control and is perfect for intermittent liquid transfers
- Included 48"- long polypropylene pick-up-tube fits 275-gallon IBC totes for easy dispensing
- Includes polypropylene adaptor that threads into 2" bung opening to hold pump system upright and secure; allows you to keep both hands free for dispensing
- Includes a flexible 5'- long PVC discharge hose



### Specifications

|                            |   |
|----------------------------|---|
| <b>Speed</b>               | Dual Speed  |
| <b>Max Flow Rate</b>       | 10 gal./Minute  |
| <b>Max Viscosity</b>       | 200 CentiPoise  |
| <b>Use With</b>            | 275 gal. IBC w/ 2" NPT Bung                                   |
| <b>Color</b>               | Black/Blue/White  |
| <b>Brand</b>               | Finish Thompson   |
| <b>Bung Opening</b>        | 2" NPT Bung   |
| <b>Compatible With</b>     | Thin-Bodied & Slightly Viscous Liquids in Non-Explosive Areas |
| <b>Explosion Proof</b>     | No  |
| <b>Horsepower</b>          | .33   |
| <b>Power Cord</b>          | 12' w/ Plug   |
| <b>Powered By</b>          | Electric  |
| <b>Temperature Limit</b>   | Maximum Temperature 150°F (66°C)                              |
| <b>Use With Flammables</b> | No  |
| <b>Sold as</b>             | 1 each  |
| <b>Weight</b>              | 10.69 lbs.  |
| <b>Composition</b>         | Motor: Steel & Plastic<br>Pick-Up Tube: Polypropylene         |

FKM  
PTFE  
ETFE  
316 Stainless Steel  
Hose: Reinforced PVC  
Drum Adapter: Polypropylene

**Includes**

1 - FTI .33 HP Electric Pump Motor (DRM1080)  
1 - 48" L FTI IBC Pick-Up Tube (IBC001)  
1 - int. dia. 0.75" x 5' L PVC Discharge Hose (DRM8011)  
1 - FTI IPS Adapter (DRM1021)

**Power Requirements**

110V/50-60 Hz

**UNSPSC**

40151529

**Pigalog® Page Number**

[Page 325](#)

**Metric Equivalent**

**Weight**

4.8 kg

**Technical Information**

**Certifications, Approvals and Ratings**

QPS Approved

**USOnly**

This product can ONLY be shipped to the United States.

**Certifications, Approvals and Ratings**

QPS Approved

**USOnly**

This product can ONLY be shipped to the United States.

**Technical Documents**

[EFP\\_FTIPumpsChemGuide](#)

[Pump Selection Guide](#)



**One Pork Avenue • Tipton, PA 16684-0304**

1-855-493-4647 • Fax: 1-800-621-7447 • [newpig.com](http://newpig.com) • [hothogs@newpig.com](mailto:hothogs@newpig.com)