

FTI .5 HP Air-Operated IBC Tote Pump System with PFP Pick-Up Tube

IBC8006 Ideal For Acids; Bases; Corrosives,Max Flow Rate 22 gal./Minute,For 275 gal. IBC Tote w/ 2" NPT Bung

Dispense mild corrosives and non-flammable liquids from 275-gallon IBC totes with this air-powered IBC pump system with poly pick-up tube.

- .5 hp, 300-6,000 RPM motor operates on 80 psi at 25 cfm and pumps up to 22 gpm; excellent for general light- to medium- viscosity jobs
- Includes 48"- long polypropylene sealless pick-up tube to fit 275-gallon IBC tanks
- Included polypropylene adaptor threads into 2" bung opening to hold pump tube upright and secure
- Includes a flexible 5'- long PVC discharge hose
- Included filter/lubricator helps ensure the long-term performance of your air pump motor



Specifications

Use With	275 gal. IBC Tote w/ 2" NPT Bung
Air Line Input Fitting	.25" Air Line Fitting
Brand	Finish Thompson
Bung Opening	2" NPT Bung
Compatible With	Acids; Bases; Other Corrosives
Explosion Proof	No
Color	Black/Blue/Silver
Horsepower	.5
Ideal For	Acids; Bases; Corrosives
Max Flow Rate	22 gal./Minute
Max Viscosity	330 CentiPoise
Powered By	Air
Power Requirements	80-100 PSI @ 15-32 CFM
Speed	Single Speed
Temperature Limit	Maximum Temperature 160°F (71°C)
Use With Flammables	No
Sold as	1 each
Weight	14.64 lbs.

Composition

Motor: Cast Iron, Aluminum

Pick-Up Tube Outer Material: Polypropylene

Shaft Material: Alloy 625

Internals: Polypropylene, PTFE, PVDF, FKM

Hose: Reinforced PVC

Drum Adapter: Polypropylene

Includes

1 - FTI .5 HP Air-Operated Pump Motor (DRM433)

1 - 48" L FTI IBC PFP Pick-Up Tube (IBC002)

1 - int. dia. 1" x 5' L PVC Discharge Hose (DRM888)

1 - FTI IPS Adapter (DRM512)

1 - FTI Filter/Lubricator (DRM434)

UNSPSC

40151529

Pigalog® Page Number

Page 338

Metric Equivalent

Weight

6.6 kg

Technical Information

USOnly

This product can ONLY be shipped to the United States.

Technical Documents

[PFP_FTIPumpsChemGuide](#)

[Pump Selection Guide](#)



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com