

# FTI .5 HP Air-Operated IBC Tote Pump System with PFS Pick-Up Tube

IBC8009 Ideal For Corrosives; Solvents, Max Flow Rate 22 gal./Minute, For 330 gal. IBC Tote w/ 2" NPT Bung

Dispense mild corrosives and non-flammable liquids from 330-gallon IBC totes with this air-powered IBC pump system with steel pick-up tube.

- .5 hp, 300-6,000 RPM motor operates on 80 psi at 25 cfm and pumps up to 22 gpm; excellent for general light- to medium- viscosity jobs
- Includes 54"- long stainless-steel pump tube that fits 330-gallon IBC tote; handles temperatures up to 220° F
- Includes 5'- long reinforced PVC discharge hose with clamp
- Included stainless steel adaptor threads into 2" bung opening to hold pump tube upright and secure
- Included filter/lubricator helps ensure the longterm performance of your air pump motor

## **Specifications**

Use With	330 gal. IBC Tote w/ 2" NPT Bung
Air Line Input Fitting	.25" Air Line Fitting
Brand	Finish Thompson
Bung Opening	2" NPT Bung
Compatible With	Mild Corrosives; Non-Flammable Solvents
Explosion Proof	No
Color	Blue/Silver
Horsepower	.5
Ideal For	Corrosives; Solvents
Max Flow Rate	22 gal./Minute
Max Viscosity	330 CentiPoise
Powered By	Air
Power Requirements	80-100 PSI @ 15-32 CFM
Speed	Single Speed
Temperature Limit	Maximum Temperature 220°F (104°C)
Use With Flammables	No
Sold as	1 each
Weight	23.77 lbs.
Composition	Motor: Cast Iron, Aluminum

	Pick-Up Tube Outer Shaft Material: 316 Stainless Steel Internals: ETFE, PTFE, Stainless Steel, FKM Hose: Reinforced PVC Drum Adapter: Stainless Steel
Includes	<ul> <li>1 - FTI .5 HP Air-Operated Pump Motor (DRM433)</li> <li>1 - 54" L FTI IBC PFS Pick-Up Tube (IBC007)</li> <li>1 - int. dia. 1" x 5' L PVC Discharge Hose (DRM888)</li> <li>1 - FTI IPS Adapter (DRM513)</li> <li>1 - FTI Filter/Lubricator (DRM434)</li> </ul>
UNSPSC	40151529
Pigalog® Page Number	Page 338

Metric Equivalent

Weight 10.8 kg

### **Technical Information**

### **USOnly**

This product can ONLY be shipped to the United States.

#### **Technical Documents**

PFS\_FTIPumpsChemGuide

Pump Selection Guide



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com