

FTI .5 HP Electric IBC Tote Pump System with PFS Pick-Up Tube

IBC8013 Ideal For Corrosives; Solvents, Max Flow Rate 20 gal./Minute, For 330 gal. IBC Tote w/ 2" NPT Bung

Dispense mild corrosives and non-flammable liquids from 330-gallon IBC totes with this high flow rate electric IBC pump system with steel pick-up tube.

- High-output, variable-speed motor (3,500rpm to 10,000rpm) offers outstanding flow control in a drip-proof design
- Pump motor is continuous duty rated for extended operation; motor shuts off if it runs too long or too hot and restarts only with manual safety reset
- Includes 54"- long stainless-steel pump tube that fits 330-gallon IBC tote; handles temperatures up to 220° F
- Includes 5'- long reinforced PVC discharge hose with clamp
- Included IPS Adapter threads into bung opening to hold pump tube upright

Specifications

Sold as

Use With	330 gal. IBC Tote w/ 2" NPT Bung
Brand	Finish Thompson
Bung Opening	2" NPT Bung
Compatible With	Mild Corrosives; Non-Flammable Solvents
Explosion Proof	No
Horsepower	.5
Color	Gray/Silver
Ideal For	Corrosives; Solvents
Max Flow Rate	20 gal./Minute
Max Viscosity	330 CentiPoise
Power Cord	12' w/ Plug
Powered By	Electric
Power Requirements	110V/50-60 Hz
Speed	Variable Speed
Temperature Limit	Maximum Temperature 220°F (104°C)
Use With Flammables	No

1 each

Weight	26.42 lbs.
Composition	Motor: Steel, Plastic Pick-Up Tube Outer Shaft Material: 316 Stainless Steel Internals: ETFE, PTFE, Stainless Steel, FKM Hose: Reinforced PVC Drum Adapter: Stainless Steel
Includes	 1 - FTI .5 HP Electric Pump Motor (DRM432) 1 - 54" L FTI IBC PFS Pick-Up Tube (IBC007) 1 - int. dia. 0.75" x 5' L PVC Discharge Hose (DRM888) 1 - FTI IPS Adapter (DRM513)
UNSPSC	40151529
Pigalog® Page Number	Page 337
Metric Equivalent	

12 kg

Technical Information

USOnly

Weight

This product can ONLY be shipped to the United States.

Certifications, Approvals and Ratings

QPS Approved

Technical Documents

PFS_FTIPumpsChemGuide

Pump Selection Guide



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com