

## PIG® Grippy® Adhesive-Backed Absorbent Mat

MAT1650 Absorbs Oils; Coolants; Solvents; Water; Universal, 16" x 50', 1 roll



Stays put no matter what™! Sticks and stays down where other absorbent mats shift or slide around; perfect for workstations or around machinery in industrial facilities.

- Adhesive-backed absorbent mat stays exactly where you put it with no shifting, bunching up or flipping over to prevent slips, trips and falls in workstations and around machinery
- Proprietary adhesive sticks to the floor with a super-tight grip, but peels up easily for quick changeouts; reduces cleanup time to make your facility more productive
- Sticks to most commercial floor surfaces including concrete, vinyl, linoleum, ceramic tile, quarry tile and laminate flooring
- Tough, spunbond top layer with heavy-duty zigzag stitching stands up to foot and light-wheeled traffic; keep mat in service until it's saturated or shows signs of wear
- Multiple layers of fine-fiber polypropylene safely absorb leaks, drips and overspray of oils, coolants, solvents and water
- Traps oil, grease and grime to keep them from being tracked around; ideal for oily areas near machines and equipment
- 16" width is great for lining workbenches, countertops and toolboxes
- Leakproof backing prevents absorbed liquid from soaking through to the floor
- Dark color hides grime so the mat looks cleaner longer
- Easy to cut and install: just roll it out, stick it down and smooth it out
- Tested and Certified by the National Floor Safety Institute (NFSI): when used as part of your floor safety program, high-traction surfaces such as PIG Grippy Absorbent Mat have been proven to reduce slip-and-fall claims by as much as 90%
- Mats take on the properties of absorbed liquids
  - always take proper precautions when handling saturated absorbents



## Specifications

<b>Dimensions</b>	16" W x 50' L
<b>Mat Weight</b>	Mediumweight
<b>Recycled Content</b>	25% or more Recycled Content
<b>Absorbency</b>	Up to 2.6 gal. per roll
<b>Brand</b>	PIG
<b>Category</b>	Grippy® Absorbent Mat
<b>Color</b>	Blue
<b>Flammability Specifications</b>	Flame Resistant - Will melt and self-extinguish
<b>Fluid Absorbed</b>	Oils; Coolants; Solvents; Water; Universal
<b>Incinerable</b>	Yes
<b>Industry</b>	Industrial Facilities; Shops & Garages
<b>Intended Use</b>	Indoor Use on Concrete, Vinyl, Linoleum, Tile and Laminate Flooring
<b>Perforated</b>	No
<b>Storage Temp Range</b>	Store between 32°F and 120°F
<b>Temperature Limit</b>	Surface temps from 55°F to 120°F
<b>Traffic</b>	Light Foot Traffic
<b>UV Resistant</b>	No
<b>Distributor Part Number</b>	10860-050;30pz34;5993048;04088x00455
<b>Sold as</b>	1 roll
<b>Weight</b>	7 lbs.
<b># per Pallet</b>	60
<b>Composition</b>	Absorbent - Polypropylene Stitching - Polyester Adhesive Backing - Proprietary Adhesive Material
<b>UNSPSC</b>	47131901
<b>Pigalog® Page Number</b>	<a href="#">Page 23</a>

## Metric Equivalent

<b>Absorbency</b>	Up to 9.8 L per roll
<b>Dimensions</b>	40.6cm W x 15m L
<b>Weight</b>	3.2 kg

## Technical Information

<b>Certifications, Approvals and Ratings</b>	
--	--

## Technical Documents

PIG Grippy® Absorbent Mat

New Pig Adhesive-Backed Mat Notice

How to use PIG Grippy Absorbent Mat

Static Coefficient Of Friction (SCOF) Testing

PIG® Grippy® Absorbent Mats

29 CFR 1910.22(a)



**New Pig**

World's best stuff for leaks, drips and spills.

**One Pork Avenue • Tipton, PA 16684-0304**

1-855-493-4647 • Fax: 1-800-621-7447 • [newpig.com](http://newpig.com) • [hothogs@newpig.com](mailto:hothogs@newpig.com)