


PIG® Paint Booth Mat with Adhesive Backing

MAT32300 Indoor Use on Concrete, Vinyl, Linoleum, Tile and Laminate Flooring, 32" x 100', 1 roll



Protects your spray booth floors and mixing room surfaces from build up by collecting the overspray, dust and particles that cause paint defects or create a fire hazard.

- Top surface helps attract and trap dust, dirt and paint and primer overspray before it causes paint defects during a spray job; mat keeps paint booth clean, bright and running efficiently
- Protect mixing room benches, tables or other work surfaces by cutting mat to the size you need
- Self-sticking adhesive back keeps mat securely in place without shifting, sliding or causing a trip hazard
- Installs quickly, peels up for fast, easy changeouts and lasts up to 3 months depending on amount of overspray and cleaning
- Durable enough for heavy foot and vehicle traffic; padding reduces noise and makes standing and kneeling more comfortable
- Bright blue and gray color options create better color matching and help to reduce casting and eliminate shadows and reflections
- Easy to control build up! No need to scrape or use chemicals to remove overspray from your floor; you can sweep or vacuum daily to remove dried overspray, dust and debris
- Helps extend the life of paint booth filters
- Apply to clean, dry surface; scrape loose build up to ensure adherence
- Not for vertical surfaces
- Add tape over the seams to reduce fraying of the edges, prevent air particulates from being trapped under the mat and help preserve the lifecycle of the mat
- Meets NFPA33 – Static Dissipative & OSHA Standards at conditions of 50% RH or higher



Item#	Description	Dimensions	Weight
-------	-------------	------------	--------

MAT32300-BL	32" W x 100' L
MAT32300-GY	32" W x 100' L

Metric Equivalent:

Item#	Description	Dimensions	Weight
MAT32300-BL		81.3cm W x 30m L	
MAT32300-GY		81.3cm W x 30m L	

Specifications

Dimensions	32" W x 100' L
Mat Weight	Mediumweight
Recycled Content	25% or more Recycled Content
Brand	PIG
Category	Paint Booth Mat
Flammability Specifications	Flame Resistant - Will melt and self-extinguish
Fluid Absorbed	Paints; Stains; Solvents
Incinerable	Yes
Industry	Automotive Painting & Refinishing
Intended Use	Indoor Use on Concrete, Vinyl, Linoleum, Tile and Laminate Flooring
Storage Temp Range	Store between 32°F and 120°F
Temperature Limit	Surface temps from 55°F to 120°F Continuous, 200°F Intermittent
Traffic	Vehicle Traffic; Heavy Foot Traffic
UV Resistant	No
Sold as	1 roll
# per Pallet	13
Composition	Absorbent - Polypropylene Stitching - Polyester Adhesive Backing - Proprietary Adhesive Material
UNSPSC	47131901
Pigalog® Page Number	Page 226

Metric Equivalent

Dimensions	81.3cm W x 30m L
-------------------	------------------

Technical Information

Certifications, Approvals and Ratings
--

NFSI Certified,ANSI B101.1- 2009

Technical Documents

PIG Grippy® Absorbent Mat

New Pig Adhesive-Backed Mat Notice

PIG® Grippy® Absorbent Mats

29 CFR 1910.22(a)(2)



New Pig

World's best stuff for leaks, drips and spills.

One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com