

## PIG® Paint Booth Mat with Adhesive Backing

MAT32350 Indoor Use on Concrete, Vinyl, Linoleum, Tile and Laminate Flooring, 32" x 150', 1 roll per box



Protects your spray booth floors and mixing room surfaces from build up by collecting the overspray, dust and particles that cause paint defects or create a fire hazard.

- Top surface helps attract and trap dust, dirt and paint and primer overspray before it causes paint defects during a spray job; mat keeps paint booth clean, bright and running efficiently
- Protect mixing room benches, tables or other work surfaces by cutting mat to the size you need
- Self-sticking adhesive back keeps mat securely in place without shifting, sliding or causing a trip hazard
- Installs quickly, peels up for fast, easy changeouts and lasts up to 3 months depending on amount of overspray and cleaning
- Durable enough for heavy foot and vehicle traffic; padding reduces noise and makes standing and kneeling more comfortable
- Bright blue and gray color options create better color matching and help to reduce casting and eliminate shadows and reflections
- Easy to control build up! No need to scrape or use chemicals to remove overspray from your floor; you can sweep or vacuum daily to remove dried overspray, dust and debris
- Helps extend the life of paint booth filters
- Apply to clean, dry surface; scrape loose build up to ensure adherence
- Not for vertical surfaces
- Add tape over the seams to reduce fraying of the edges, prevent air particulates from being trapped under the mat and help preserve the lifecycle of the mat
- Meets NFPA33 – Static Dissipative & OSHA Standards at conditions of 50% RH or higher



MAT32350-BL	32" W x 150' L	41.15 lbs.
MAT32350-GY	32" W x 150' L	41.15 lbs.

## Metric Equivalent:

Item#	Description	Dimensions	Weight
MAT32350-BL		81cm W x 46m L	18.7 kg
MAT32350-GY		81cm W x 46m L	18.7 kg

## Specifications

<b>Dimensions</b>	32" W x 150' L
<b>Mat Weight</b>	Mediumweight
<b>Recycled Content</b>	25% or more Recycled Content
<b>Brand</b>	PIG
<b>Category</b>	Paint Booth Mat
<b>Flammability Specifications</b>	Flame Resistant - Will melt and self-extinguish
<b>Fluid Absorbed</b>	Paints; Stains; Solvents
<b>Incinerable</b>	Yes
<b>Industry</b>	Automotive Painting & Refinishing
<b>Intended Use</b>	Indoor Use on Concrete, Vinyl, Linoleum, Tile and Laminate Flooring
<b>Storage Temp Range</b>	Store between 32°F and 120°F
<b>Temperature Limit</b>	Surface temps from 55°F to 120°F Continuous, 200°F Intermittent
<b>Traffic</b>	Vehicle Traffic; Heavy Foot Traffic
<b>UV Resistant</b>	No
<b>Sold as</b>	1 roll per box
<b>Weight</b>	41.15 lbs.
<b># per Pallet</b>	12
<b>Composition</b>	Absorbent: Polypropylene Stitching: Polyester Adhesive Backing: Proprietary Adhesive Material
<b>UNSPSC</b>	47131901
<b>Pigalog® Page Number</b>	<a href="#">Page 28</a>

## Metric Equivalent

<b>Weight</b>	18.7 kg
<b>Dimensions</b>	81cm W x 46m L

## Technical Information

### Certifications, Approvals and Ratings

NFSI Certified,ANSI B101.1- 2009,ANSI/ESD STM11.11,MIL-STD-3010C

## Technical Documents

PIG Grippy® Absorbent Mat

The Complete Slip, Trip & Fall Risk Zone Audit

New Pig Adhesive-Backed Mat Notice

Instructions for PIG Grippy Mat Cleaning & Care Guide

White Paper- Getting a Grip on Slips, Trips and Falls

White Paper- The Walk Zone Safety Report

PIG® Grippy® Absorbent Mats

29 CFR 1910.22(a)(2)



**One Pork Avenue • Tipton, PA 16684-0304**

1-855-493-4647 • Fax: 1-800-621-7447 • [newpig.com](http://newpig.com) • [hothogs@newpig.com](mailto:hothogs@newpig.com)