

PIG® Industrial Absorbent Adhesive-Backed Grippy® Floor Mat

MAT3251 Absorbs Oils; Coolants; Solvents; Water; Universal, 32" x 40", 1 roll



Stays put no matter what™! Sticks and stays down where other absorbent mats shift or slide around; perfect for workstations or around machinery in industrial facilities.

- PIG Industrial Absorbent Grippy Mat stays exactly where you put it with no shifting or bunching up underfoot
- Fits perfectly underneath vehicles to protect shop floors from oily leaks and drips; reduces cleanup time to keep your shop productive
- Sticks to most commercial floor surfaces including concrete, vinyl, linoleum, ceramic tile, quarry tile and laminate flooring
- Proprietary adhesive sticks to the floor with a super-tight grip, but can be easily removed and repositioned so you can reuse the mat until it becomes saturated
- Tough, spunbond top layer with heavy-duty zigzag stitching stands up to rolling tires and service bay foot traffic
- Multiple layers of fine-fiber polypropylene safely absorb and retains oils, coolants, water, grease, gasoline, solvents, auto fluids, paint overspray, battery acid and most other liquids
- Leakproof backing prevents absorbed liquid from soaking through to the floor
- Dark color hides grime so the mat looks cleaner longer
- Mat ends are heat-cut for a finished, professional look
- Tested and Certified by the National Floor Safety Institute (NFSI): when used as part of your floor safety program, high-traction surfaces such as PIG Industrial Absorbent Grippy Mat have been proven to reduce slip-and-fall claims by as much as 90%
- Mats take on the properties of absorbed liquids
 - always take proper precautions when handling saturated absorbents



Absorbency Range	0 - 0.9 gal.
Dimensions	32" W x 40" L
Mat Weight	Mediumweight
Recycled Content	25% or more Recycled Content
Absorbency	Up to .35 gal. per roll
Brand	PIG
Color	Blue
Category	Grippy® Industrial Absorbent Mat
Flammability Specifications	Flame Resistant - Will melt and self-extinguish
Fluid Absorbed	Oils; Coolants; Solvents; Water; Universal
Incinerable	Yes
Industry	Industrial Facilities; Shops & Garages
Intended Use	Indoor Use on Concrete, Vinyl, Linoleum, Tile and Laminate Flooring
Perforated	No
Storage Temp Range	Store between 32°F and 120°F
Temperature Limit	Surface temps from 55°F to 120°F
Traffic	Light Foot Traffic
UV Resistant	No
Sold as	1 roll
Weight	1.8 lbs.
# per Pallet	500

Composition	Absorbent: Polypropylene Stitching: Polyester Adhesive Backing: Proprietary Adhesive Material
--------------------	---

UNSPSC	47131901
---------------	----------

Pigalog® Page Number	Page 25
-----------------------------	-------------------------

Metric Equivalent

Absorbency	Up to 1.3 L per roll
Weight	.8 kg
Dimensions	81cm W x 102cm L

Technical Information

Certifications, Approvals and Ratings	NFSI Certified,ANSI B101.1- 2009,ANSI/ESD STM11.11,MIL-STD-3010C
--	--

Technical Documents

[PIG Grippy® Absorbent Mat](#)

[The Complete Slip, Trip & Fall Risk Zone Audit](#)

How to use PIG Grippy Absorbent Mat

Instructions for PIG Grippy Mat Cleaning & Care Guide

Static Coefficient Of Friction (SCOF) Testing

White Paper- Getting a Grip on Slips, Trips and Falls

White Paper- The Walk Zone Safety Report

PIG® Grippy® Absorbent Mats

29 CFR 1910.22(a)(2)



New Pig

World's best stuff for leaks, drips and spills.

One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com