

## **PIG® Stat-Mat® Absorbent Roll**

MAT402 Heavyweight, 30" x 150', 1 roll per bag

The ONLY absorbent mat for fuels and solvents proven to dissipate static.



- The best mat you can buy to reduce the risk of electrostatic discharge; a critical precaution around flammable liquids and vapors
- Stat-Mat Pads and Rolls pass ANSI and MIL spec standards for static decay and surface resistivity, making them perfect for fueling areas and solvent cleanup
- Absorbs and retains oils and fuels - including acetone, benzene, gasoline, toluene, xylene, mineral spirits and jet fuels - but not water
- Lasts 2X longer than ordinary mats for fewer change-outs; Multiple layers of 100% polypropylene are thermally bonded to make PIG Mat the strongest mat on the market; won't rip, tear or fray even when saturated
- Exclusive dimple pattern speeds wicking of liquid throughout mat for faster, easier cleanup
- Highly absorbent, fine-fiber construction won't leave behind oil or fiber residue
- Packaged in special static-dissipative bags to help reduce static charge buildup
- Floats to clean up spills on water
- White color tells you it's only for oils and fuels
- Rolls are ideal for covering large areas and soaking up leaks and overspray
- Easy-tear perforations let you take only what you need, so you use less mat and save money
- Heavy-weight construction is highly durable and absorbent for demanding tasks and large-volume cleanups
- Mats take on the properties of absorbed liquids
  - always take proper precautions when handling saturated absorbents



### Specifications

<b>Dimensions</b>	30" W x 150' L
<b>Mat Weight</b>	Heavyweight
<b>Absorbency</b>	Up to 40.2 gal. per bag
<b>Absorbency per</b>	Up to 40.2 gal. per roll

<b>Brand</b>	PIG
<b>Category</b>	Static-Dissipative Mat
<b>Color</b>	White
<b>Core Diameter</b>	1.5"
<b>Floating</b>	Yes
<b>Flammability Specifications</b>	Flame Resistant - Will melt and self-extinguish
<b>Fluid Absorbed</b>	Oils; Fuels; Oil-Based Liquids (Not Water)
<b>Incinerable</b>	Yes
<b>Indoor/Outdoor</b>	Indoor Use; Short-Term Outdoor Use
<b>Perforated</b>	Yes
<b>Perforated Pattern</b>	10" x 15" sections
<b>Reusable</b>	No
<b>Static-Dissipative</b>	Yes
<b>Traffic</b>	Not Recommended for Foot Traffic
<b>UV Resistant</b>	No
<b>Wringable</b>	No
<b>Distributor Part Number</b>	89073-838;30ra46;2422438;04088x31435
<b>Sold as</b>	1 roll per bag
<b>Weight</b>	30 lbs.
<b># per Pallet</b>	12
<b>Composition</b>	Polypropylene
<b>UNSPSC</b>	47131901
<b>Pigalog® Page Number</b>	<a href="#">Page 45</a>

## Metric Equivalent

<b>Absorbency</b>	Up to 152.2 L per bag
<b>Absorbency per</b>	Up to 152.2 L per roll
<b>Dimensions</b>	76.2cm W x 46m L
<b>Weight</b>	13.6 kg

## Technical Information

### Certifications, Approvals and Ratings

ANSI/ESD STM11.11,MIL-STD-3010C

### Technical Documents

[PIG® Oil-Only Absorbents](#)

[29 CFR 1910.106\(h\)\(7\(i\)\(a\)\)](#)

[29 CFR 1910.22\(a\)\(2\)](#)

[40 CFR 112.7](#)



**One Pork Avenue • Tipton, PA 16684-0304**

1-855-493-4647 • Fax: 1-800-621-7447 • [newpig.com](http://newpig.com) • [hothogs@newpig.com](mailto:hothogs@newpig.com)