

## PIG® Stat-Mat® Absorbent Roll

MAT420 Heavyweight, 15" W x 150' L, 2 rolls per bag



The ONLY absorbent mat for fuels and solvents proven to dissipate static.

- The best mat you can buy to reduce the risk of electrostatic discharge; a critical precaution around flammable liquids and vapors
- Stat-Mat Pads and Rolls pass ANSI and MIL-SPEC standards for static decay and surface resistivity, making them perfect for fueling areas and solvent cleanup
- Absorbs and retains oils and fuels - including acetone, benzene, gasoline, toluene, xylene, mineral spirits and jet fuels - but not water
- Lasts 2X longer than ordinary mats for fewer change-outs; Multiple layers of 100% polypropylene are thermally bonded to make PIG Mat the strongest mat on the market; won't rip, tear or fray even when saturated
- Exclusive dimple pattern speeds wicking of liquid throughout mat for faster, easier cleanup
- Highly absorbent, fine-fiber construction won't leave behind oil or fiber residue
- Packaged in special static-dissipative bags to help reduce static charge buildup
- Absorbent spill pad floats to clean up spills on water
- White color tells you it's only for oils and fuels
- Rolls are ideal for covering large areas and soaking up leaks and overspray
- Easy-tear perforations let you take only what you need, so you use less mat and save money
- Heavy-weight construction is highly durable and absorbent for demanding tasks and large-volume cleanups
- Mats take on the properties of absorbed liquids
  - always take proper precautions when handling saturated absorbents



### Specifications

Absorbency Range	40 - 49.9 gal.
Dimensions	15" W x 150' L
Mat Weight	Heavyweight

<b>Absorbency</b>	Up to 40.2 gal. per bag
<b>Absorbency per</b>	Up to 20.1 gal. per roll
<b>Brand</b>	PIG
<b>Color</b>	White
<b>Category</b>	Static-Dissipative Mat
<b>Core Diameter</b>	1.5"
<b>Flammability Specifications</b>	Flame Resistant - Will melt and self-extinguish
<b>Floating</b>	Yes
<b>Fluid Absorbed</b>	Oils; Fuels; Oil-Based Liquids (Not Water)
<b>Indoor/Outdoor</b>	Indoor Use; Short-Term Outdoor Use
<b>Incinerable</b>	Yes
<b>Perforated</b>	Yes
<b>Perforated Pattern</b>	10" x 15" sections
<b>Reusable</b>	No
<b>Static-Dissipative</b>	Yes
<b>Traffic</b>	Not Recommended for Foot Traffic
<b>UV Resistant</b>	No
<b>Wringable</b>	No
<b>Sold as</b>	2 rolls per bag
<b>Weight</b>	30 lbs.
<b># per Pallet</b>	12
<b>Composition</b>	Polypropylene
<b>UNSPSC</b>	47131901
<b>Pigalog® Page Number</b>	<a href="#">Page 43</a>

## Metric Equivalent

<b>Absorbency per</b>	Up to 76.1 L per roll
<b>Absorbency</b>	Up to 152.2 L per bag
<b>Weight</b>	13.6 kg
<b>Dimensions</b>	38cm W x 46m L

## Technical Information

### Certifications, Approvals and Ratings

ANSI/ESD STM11.11,MIL-STD-3010C

### Technical Documents

Technical Data Sheet for PIG® Oil Only Absorbents

29 CFR 1910.106(e)(6)(i)

29 CFR 1910.22(a)(2)

40 CFR 112.7

40 CFR 122.26



**One Pork Avenue • Tipton, PA 16684-0304**

1-855-493-4647 • Fax: 1-800-621-7447 • [newpig.com](http://newpig.com) • [hothogs@newpig.com](mailto:hothogs@newpig.com)