

PIG® Stat-Mat® Absorbent Bib

MAT4430 Absorbs Oils; Fuels; Oil-Based Liquids (Not Water), For Small Engine Applications, .75" to 3" Dia. Opening Dimensions



Catch drips and splashes safely while filling your fuel tank by placing this anti-static absorbent bib around the fill opening.

- Keep your tank and ground clean by catching drips and splashes with this bib that's made to fit around fill openings
- Fits over a wide variety of fill openings
- Pad is easily removable to prevent damage to surrounding areas and for fast, easy cleanup
- Absorbs and retains oils and fuels, including acetone, benzene, gasoline, toluene, xylene, mineral spirits and jet fuels; repels water without absorbing it
- Stat-Mat material reduces the risk of electrostatic discharge, a critical precaution around flammable liquids and vapors
- Packaged in a special static-dissipative bag to help reduce static-charge buildup
- Mats take on the properties of absorbed liquids, so always take proper precautions when handling saturated absorbents
- Area around fill neck must be cool before placing mat



Specifications

Absorbency Range	0 - 0.9 gal.
Use With	Small Engine Applications
Dimensions	5" W x 8.5" L
Mat Weight	Lightweight
Absorbency	Up to 17.43 oz. per bag
Absorbency per	Up to 1.74 oz. per pad
Color	White
Brand	PIG
Category	Static-Dissipative Fuel Absorbent Bib
Flammability Specifications	Flame Resistant - Will melt and self-extinguish
Fluid Absorbed	Oils; Fuels; Oil-Based Liquids (Not Water)

Incinerable	Yes
Opening Dimensions	.75" to 3" Dia.
Reusable	No
Static-Dissipative	Yes
UV Resistant	No
Wringable	No
Sold as	10 pads per bag
Weight	.2 lbs.
Composition	Polypropylene
UNSPSC	47131901
Pigalog® Page Number	<u>Page N5</u>

Metric Equivalent

Absorbency per	Up to 51.5 mL per pad
Absorbency	Up to 515.4 mL per bag
Weight	91 g
Dimensions	13cm W x 22cm L

Technical Information



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com