

## PIG® Collapse-A-Tainer® Self-Rising Spill Containment Berm



PAK1002 Ideal For Large Vehicles, Drive-Through, 12' W x 28' L x 1' H Sump, Sump Capacity 2513 gal.

Containment system can be staked down and provides easy drive-in access without having to manually fold up sidewalls when you drive out.

- Endwalls can remain folded down during normal use, but automatically rise with the liquid level when a leak occurs
- Heavy-duty hinges can be manually locked into place when snow, hoses or other heavy objects could prevent the flotation system from functioning
- Right-angle hinge design allows more unobstructed working space on interior of unit
- Brackets remain out of the way to avoid breakage from accidental impact or driveovers
- Folds to a compact size to let you store the system in a vehicle and transport it to a remote location; included strap secures unit in place
- Constructed of durable, XR-5 to resist chemicals, abrasion and tearing
- Grommets at each support hinge allow unit to be staked to the ground when needed
- Ideal under storage tanks, pillow tanks, pallets loaded with drums and more
- Custom sizes and colors available; call 1-800-HOT-HOGS (468-4647) for details



### Specifications

Sump Capacity Range	1000 gal. or more
Dimensions	12.75' W x 28.75' L x 1' H
Sump Capacity	2513 gal.
Brand	PIG
Folded Dimensions	2.67' W x 2.67' L x 1' H Folded
Ideal For	Large Vehicles, Drive-Through
Color	Black/Yellow
Sump Dimensions	12' W x 28' L x 1' H
Traffic	Vehicle Traffic
Wall Type	Manual; Self-Rising
Sold as	1 each
Weight	147 lbs.

New Pig Patent	10,024,486
Composition	XR-5® 30 mil
UNSPSC	24111812
Pigalog® Page Number	<u>Page 391</u>

Metric Equivalent

Sump Capacity	9511.7 L
Weight	66.7 kg
Dimensions	3.9m W x 8.8m L x 30cm H

Technical Information

Technical Documents

- PIG Collapse-A-Tainer with XR-5®
- How to Measure for PIG® Collapse-a-tainer® Containment System
- Instructions for PIG Collapse-A-Tainer Spill Containment Berm
- 40 CFR 112.7
- 40 CFR 122.26
- 40 CFR 264.175



**One Pork Avenue • Tipton, PA 16684-0304**  
1-855-493-4647 • Fax: 1-800-621-7447 • [newpig.com](http://newpig.com) • [hothogs@newpig.com](mailto:hothogs@newpig.com)