

PIG® 2-Drum Steel Spill Containment Pallet

PAK239 Holds (2) 55 gal. Steel Drums, 35" x 53.75" x 12.375", Sump Capacity 66 gal.

Heavy duty, 12-gauge steel pallet is designed for secondary containment of flammable liquids to stay in compliance.

- Can be bonded and grounded to control static electricity and prevent sparking while transferring or storing flammables
- Catches leaks and spills to help you comply with regs and keep floors slip-free
- Powder-coating guards against rust and corrosion
- Included .5" NPT drain plug lets you empty sump without removing drums; grating is removable for easy clean-up
- 4-way forklift access (move unloaded only)



Specifications

Sump Capacity Range	40 - 69.9 gal.
Dimensions	35" W x 53.75" L x 12.375" H
Load Capacity UDL	2500 lbs.
Sump Capacity	66 gal.
Brand	PIG
Drain	Includes .5" NPT Drain
Color	Black
Double-Stackable Unit	No
Grates	(1) 53.75" L x 35" W Grate
Fork Truck Access	Four-Way Fork Access, Move Unloaded Only
Holds	(2) 55 gal. Steel Drums
Material	Steel
Use With Flammables	Yes
Sold as	1 each

Weight	180 lbs.
# per Pallet	4
Composition	Powder-Coated 12 Gauge Steel
UNSPSC	24101905
Pigalog® Page Number	<u>Page 351</u>

Metric Equivalent

Sump Capacity	249.8 L
Load Capacity UDL	1134 kg
Weight	81.6 kg
Dimensions	89cm W x 137cm L x 31cm H

Technical Information

Certifications, Approvals and Ratings

UFC Article 79 Section 7901.10

Technical Documents

40 CFR 112.7

40 CFR 122.26

40 CFR 264.175



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com