

PIG™ 2-Drum Steel Modular Spill Deck

PAK645 Holds (2) 55 gal. Steel Drums, 25.75" x 51.5" x 4", Sump Capacity 17.5 gal.

Create a custom storage area for chlorinated solvents and other flammables with the sump capacity you need to comply with regs.

- Patented "flow-through" sump design lets liquid pass freely from one sump to another to help you comply with containment regulations
- Modular design features exclusive bulkhead fittings and predrilled ports to connect to other decks; ready to use as soon as they arrive
- Special wrench (included) makes it easy to connect multiple deck sections
- Durable 11-gauge hot-rolled steel is powder coated for extended life
- Super-low 4" height is easy to load or unload; pumps and funnels are easy to access
- Drums can be bonded and grounded to the deck for safer storage of flammable liquids
- Grating features raised drain-hole edges for non-slip footing
- We test all of our Containment Deck designs at max load for months to ensure they can handle full capacity at your facility



Specifications

Sump Capacity Range	10 - 19.9 gal.
Dimensions	25.75" W x 51.5" L x 4" H
Load Capacity UDL	16000 lbs.
Sump Capacity	17.5 gal.
Brand	PIG
Drain	None
Color	Black
Double-Stackable Unit	No
Grates	(2) 25.75" L x 25.75" W Grates
Fork Truck Access	No Fork Truck Access
Holds	(2) 55 gal. Steel Drums
Material	Steel
Use With Flammables	Yes

Sold as	1 each
Weight	126 lbs.
New Pig Patent	5,562,047; Foreign Patents
# per Pallet	10
Composition	Deck: 11 Gauge Hot-Rolled Steel Gaskets: Neoprene
UNSPSC	24101905
Pigalog® Page Number	<u>Page 351</u>

Metric Equivalent

Sump Capacity	66.2 L
Load Capacity UDL	7257.6 kg
Weight	57.2 kg
Dimensions	65cm W x 131cm L x 10cm H

Technical Information

Certifications, Approvals and Ratings

UFC Article 79 Section 7901.10

Technical Documents

Instructions for Connecting Two 2-Drum Modular Spill Decks

40 CFR 112.7

40 CFR 122.26

40 CFR 264.175



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com