

PIG® 1-Drum Steel Modular Spill Deck

PAK646 Holds (1) 55 gal. Steel Drum, 25.75" W x 25.75" L x 4" H, Sump Capacity 8.75 gal.



Create a custom storage area for chlorinated solvents and other flammables with the sump capacity you need to comply with regs.

- Patented "flow-through" sump design lets liquid pass freely from one sump to another to help you comply with containment regulations
- Modular design features exclusive bulkhead fittings and predrilled ports to connect to other decks; ready to use as soon as they arrive
- Special wrench (included) makes it easy to connect multiple deck sections
- Durable 11-gauge hot-rolled steel is powder coated for extended life
- Super-low 4" height is easy to load or unload; pumps and funnels are easy to access
- Drums can be bonded and grounded to the deck for safer storage of flammable liquids
- Grating features raised drain-hole edges for non-slip footing
- We test all of our Containment Deck designs at max load for months to ensure they can handle full capacity at your facility



Specifications

Sump Capacity Range	1 - 9.9 gal.
Dimensions	25.75" W x 25.75" L x 4" H
Load Capacity UDL	8000 lbs.
Sump Capacity	8.75 gal.
Brand	PIG
Drain	No
Color	Black
Double-Stackable Unit	No
Grates	(1) 25.75" L x 25.75" W Grate
Fork Truck Access	No Fork Truck Access
Holds	(1) 55 gal. Steel Drum
Material	Steel
Use With Flammables	Yes

Sold as	1 each
Weight	67 lbs.
New Pig Patent	5,562,047; Foreign Patents
# per Pallet	10
Composition	Deck: 11 Gauge Hot-Rolled Steel Gaskets: Neoprene
UNSPSC	24101905
Pigalog® Page Number	<u>Page 373</u>

Metric Equivalent

Sump Capacity	33.1 L
Load Capacity UDL	3628.8 kg
Weight	30.4 kg
Dimensions	65cm W x 65cm L x 10cm H

Technical Information

Certifications, Approvals and Ratings
--

UFC Article 79 Section 7901.10

Technical Documents

[Instructions for Connecting Two 1-Drum Modular Spill Decks](#)

[40 CFR 112.7](#)

[40 CFR 122.26](#)

[40 CFR 264.175](#)



New Pig

World's best stuff for leaks, drips and spills.

One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com