

## PIG® Poly IBC Spill Containment Pallet

PAK735 Holds (1) IBC, 62" x 62" x 26", 360 gal. Sump Capacity



You can't buy a stronger pallet to store your totes in compliance. PIG is the toughest on the market.

- Strong enough for long-term storage of IBCs, this innovative design transfers weight to load bearing channels to maximize capacity
- Molded-in sump catches leaks, drips and spills to help you comply with regulations and keep storage areas clean
- Low-density polyethylene (LDPE) construction resists UV rays, rust, corrosion and most chemicals
- Textured grating holds a variety of IBC sizes; lifts out for easy access to sump
- Low profile for easy access to and dispensing from IBC tanks
- Two-way forklift entry allows movement from either direction when not loaded
- Optional .75" drain plug lets you empty sump without removing drums or grating



| Item#         | Description          | Dimensions            | Weight   |
|---------------|----------------------|-----------------------|----------|
| PAK735-BK-WD  | Black, With Drain    | 62" W x 62" L x 26" H | 419 lbs. |
| PAK735-BK-WOD | Black, Without Drain | 62" W x 62" L x 26" H | 419 lbs. |

### Metric Equivalent:

| Item#         | Description          | Dimensions                     | Weight   |
|---------------|----------------------|--------------------------------|----------|
| PAK735-BK-WD  | Black, With Drain    | 157.5cm W x 157.5cm L x 66cm H | 190.1 kg |
| PAK735-BK-WOD | Black, Without Drain | 157.5cm W x 157.5cm L x 66cm H | 190.1 kg |

### Specifications

|                          |   |
|--------------------------|---|
| <b>Holds</b>             | (1) IBC                                   |
| <b>Dimensions</b>        | 62" W x 62" L x 26" H                     |
| <b>Recycled Content</b>  | 27% Post-Industrial Recycled Polyethylene |
| <b>Load Capacity UDL</b> | 8000 lbs.                                 |
| <b>Sump Capacity</b>     | 360 gal.                                  |
| <b>Brand</b>             | PIG                                       |

|                              |   |
|------------------------------|---|
| <b>Double-Stackable Unit</b> | No                                      |
| <b>Drain</b>                 | Optional .75" Drain                     |
| <b>Fork Truck Access</b>     | Two-Way Fork Access, Move Unloaded Only |
| <b>Grates</b>                | (2) 52" L x 26" W Grates                |
| <b>Use With Flammables</b>   | No                                      |
| <b>Sold as</b>               | 1 each                                  |
| <b>Weight</b>                | 419 lbs.                                |
| <b># per Pallet</b>          | 3                                       |
| <b>Composition</b>           | Polyethylene                            |
| <b>UNSPSC</b>                | 24101905                                |
| <b>Pigalog® Page Number</b>  | <u>Page 377</u>                         |

## Metric Equivalent

|                          |                                |
|--------------------------|--------------------------------|
| <b>Dimensions</b>        | 157.5cm W x 157.5cm L x 66cm H |
| <b>Load Capacity UDL</b> | 3628.8 kg                      |
| <b>Sump Capacity</b>     | 1362.6 L                       |
| <b>Weight</b>            | 190.1 kg                       |

## Technical Information

### Technical Documents

[LDPE Products](#)

[40 CFR 112.7](#)

[40 CFR 122.26](#)

[40 CFR 264.175](#)

### Disclaimers

#### Flammables Notice

If using this product with flammable liquids, please consider the regulations that apply to storage and handling of flammable liquids and the safety of this application, specifically flammable vapors, static discharge and heat sources. For further assistance, please call Technical Services.



**One Pork Avenue • Tipton, PA 16684-0304**

1-855-493-4647 • Fax: 1-800-621-7447 • [newpig.com](http://newpig.com) • [hothogs@newpig.com](mailto:hothogs@newpig.com)