



PIG® Build-A-Berm® Barrier T Connector

PLR132 For 4" High Build-A-Berm Barrier,2 per box

Customize a semi-permanent barrier layout, including the option for dual containment areas separated by a shared center line, using these crush-resistant T Connectors as part of your PIG Spill Berm design.

- Contain leaks and spills around your unique machinery setup or storage area dimensions without building expensive concrete curbs or cutting and installing angle iron
- Barriers can be constructed into a semipermanent, high-visibility barrier that's exactly the size and shape you need; build it indoors or out
- Can be used to help create two separate containment areas with a shared center line in order to take up less floor space
- Durable, 18 oz all-vinyl covering resists oils, coolants and most chemicals
- Pliable open-cell foam barrier springs back into shape after you walk or roll over it with light, wheeled equipment
- Can be cut to length with utility knife; for best installation results, secure to a smooth, sealed surface with sealant (sold separately) and join seams with vinyl cement (sold separately)
- High-visibility yellow color draws attention to barrier for increased safety
- Easy removal requires only a flat-bladed shovel
- Great for use around battery charging stations, machinery or any other leak-prone areas

Specifications

| Style | T Connector |
|-------------------|------------------------------|
| Use With | 4" High Build-A-Berm Barrier |
| Dimensions | 12.5" W x 18.5" L x 1.5" H |
| Barrier Height | 4" H |
| Brand | PIG |
| Temperature Limit | Works from -22°F to 160°F |
| Color | Yellow |
| Traffic | Cart Traffic |
| Sold as | 2 per box |
| Weight | 2.25 lbs. |

| New Pig Patent | 5,820,297 |
|--|--|
| Composition | Cover: 18 oz. PVC Core: Open-Cell Polyurethane Foam |
| UNSPSC | 24101907 |
| Metric Equivalent | |
| Weight | 1 kg |
| Dimensions | 32cm W x 47cm L x 3.8cm H |
| Technical Information | |
| USOnly | |
| This product can ONLY be shipped to the United States. | |
| Technical Documents | |
| PIG Build-A-Berm® Barrier | |
| Instructions for Using PIG® Build-A-Berm® Barrier | |
| 40 CFR 112.7 | |
| 40 CFR 122.26 | |
| 40 CFR 264.175 | |



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com